

Produktinformation



Information

<i>Tillverkare</i>	AOC
<i>Artnr</i>	I1601FWUX

AOC I1601FWUX - LED monitor - Full HD (1080p) - 15.6"

The updated portable USB Type-C is sleeker in design and utilizes the advanced USB Type-C port for connecting to your PC or laptop. USB Type-C allows both power and data streams simultaneously. IPS panels have excellent color uniformity at any viewing angle, such as a perfect supermodel without flaws. AOC LowBlue mode technology is a software solution that decreases harmful blue light by controlling color temperatures without compromising the naturally vivid colors of the IPS panel.

Specifikation

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Diagonal Size	15.6"
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 60 Hz
Pixel Pitch	0.17925 mm
Brightness	220 cd/m ²
Contrast Ratio	700:1
Colour Support	262,000 colours
Response Time	5 ms (grey-to-grey)
Vertical Refresh Rate	50 - 76 Hz
Horizontal Refresh Rate	30 - 83 kHz
Horizontal Viewing Angle	160
Vertical Viewing Angle	160
Backlight Technology	LED backlight
OSD Languages	English, French, Spanish
Features	Ultra Slim Design, USB bus powered, Low Blue Light Mode, auto-rotation, Wide Viewing Angle, foldable stand

Colour	Black & silver
Dimensions (WxDxH)	37.62 cm x 0.85 cm x 23.52 cm
Weight	824 g

Connectivity

Interfaces	USB-C
-------------------	-------

Mechanical

Display Position Adjustments	Pivot (rotation), tilt
Tilt Angle	+5/+25

Miscellaneous

Included Accessories	Flexi-Stand Smart Cover
Cables Included	1 x USB-C cable
Compliant Standards	FCC, RoHS, cTUVus, EPA, DDC-2B/CI

Power

Power Consumption Operational	8 Watt
Power Consumption Stand by	0.5 Watt

Software / System Requirements

OS Required	Windows 8 / 10, Apple macOS 10.12.1 or later
--------------------	--

Dimensions & Weight (Shipping)

Shipping Width	8.4 cm
Shipping Depth	29.5 cm
Shipping Height	44.2 cm
Shipping Weight	1.547 kg

Environmental Standards

ENERGY STAR Certified	Yes
------------------------------	-----

Manufacturer Warranty

Service & Support	Limited warranty - 3 years
------------------------------	----------------------------

Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 85% (non-condensing)