

## Produktinformation



### Information

|                    |                  |
|--------------------|------------------|
| <i>Tillverkare</i> | Allied Telesis   |
| <i>Artnr</i>       | AT-2711FX/SC-901 |

## Allied Telesis AT-2711FX/SC - Network adapter - PCIe - 10/100 Ethernet - federal government

AT-2711FX 1x PCI-Express design gives you the maxim possible bandwidth and bus efficiency, Hot Swappable capability and Low Power Consumption. The priority queuing and virtual LAN features offered by AT-2711FX can help users set up the network based on their own needs. The comprehensive diagnostics and configuration software suite provides system administrators and engineers with a profound tool to analyze the network adapter and check specific data. AT-2711FX Fast Ethernet Fiber Adapter comes with a variety of reliability features. They aim at maintaining a connection as long as possible. This is reached by link aggregation, heterogeneous mixed-speed failover and hot swap.

## Specifikation

### General

|                             |                 |
|-----------------------------|-----------------|
| <b>Device Type</b>          | Network adapter |
| <b>Form Factor</b>          | Plug-in card    |
| <b>Interface (Bus) Type</b> | PCI Express x1  |

### Networking

|                                   |  |
|-----------------------------------|--|
| <b>Ports</b>                      | 10/100 Ethernet  |
| <b>Connectivity Technology</b>    | Wired  |
| <b>Cabling Type</b>               | Ethernet 100Base-FX  |
| <b>Data Link Protocol</b>         | Fast Ethernet  |
| <b>Data Transfer Rate</b>         | 100 Mbps   |
| <b>Max Transfer Distance</b>      | 2 km   |
| <b>Remote Management Protocol</b> | SNMP   |
| <b>Status Indicators</b>          | Link OK, link/activity   |
| <b>Features</b>                   | Flow control, ACPI support, wake on LAN (WOL), IPv6 support, half duplex mode, full duplex mode, Quality of Service (QoS), PXE support |
| <b>Compliant Standards</b>        | IEEE 802.2, IEEE 802.3u, IEEE 802.1p, IEEE 802.1x, IEEE 802.3ac  |

### Processor / Memory

|                                  |  |
|----------------------------------|--|
| <b>Processor</b>                 | 1 x Broadcom BCM5752   |
| <b>RAM</b>                       | 72 KB  |
| Expansion / Connectivity         |  |
| <b>Interfaces</b>                | 1 x 100Base-FX - SC multi-mode - x 2   |
| <b>Compatible Slots</b>          | 1 x PCI Express x1   |
| Miscellaneous                    |  |
| <b>Included Accessories</b>      | Low-profile bracket, full-height bracket   |
| <b>Compatible with Windows 7</b> | "Compatible with Windows 7" software and devices carry Microsoft's assurance that these products have passed tests for compatibility and reliability with 32-bit and 64-bit Windows 7. |
| <b>Compliant Standards</b>       | FCC Class B certified, UL, TUV, VCCI, C-Tick, EN55024, EN55022 Class B, RoHS   |
| <b>Pricing Type</b>              | Federal government   |
| <b>TAA Compliant</b>             | Yes  |
| Software / System Requirements   |  |
| <b>OS Required</b>               | Novell NetWare 6.x, Linux 2.4, Microsoft Windows Server 2003, Linux 2.6, Microsoft Windows 2000/XP/Vista/7, Microsoft Windows Server 2008  |
| Dimensions & Weight              |  |
| <b>Depth</b>                     | 12.1 cm  |
| <b>Height</b>                    | 6.9 cm   |
| <b>Weight</b>                    | 50 g   |
| Manufacturer Warranty            |  |
| <b>Service &amp; Support</b>     | Limited warranty - 5 years   |
| Environmental Parameters         |  |
| <b>Min Operating Temperature</b> | 0 °C   |
| <b>Max Operating Temperature</b> | 50 °C  |
| <b>Humidity Range Operating</b>  | 5 - 90% (non-condensing)   |