

Produktinformation



Information

<i>Tillverkare</i>	Allied Telesis
<i>Artnr</i>	AT-2911SX/ST-901

Allied Telesis AT-2911SX/ST - Network adapter - PCIe low profile - 1000Base-SX - 850 nm - federal government

Allied Telesis 2911 series Network Interface Cards feature a PCI Express (PCIe x1) design, providing the maximum possible bandwidth and bus efficiency while providing the benefits of low power consumption.

Specifikation

General

Device Type	Network adapter
Form Factor	Plug-in card - low profile
Interface (Bus) Type	PCI Express x1

Networking

Ports	1000Base-SX
Connectivity Technology	Wired
Cabling Type	Ethernet 1000Base-SX
Data Link Protocol	Gigabit Ethernet
Data Transfer Rate	1 Gbps
Optical Wave Length	850 nm
Network / Transport Protocol	TCP/IP
Remote Management Protocol	SNMP
Status Indicators	Link/activity
Features	Flow control, auto-negotiation, VLAN support, IPv6 support, Quality of Service (QoS), Jumbo Frames support, Receive Side Scaling (RSS), Link Aggregation Control Protocol (LACP), Energy Efficient Ethernet, Forward Error Correction (FEC), Smart Load Balancing (SLB), checksum offload support, Extended Message-Signaled Interrupts (MSI-X), iSCSI remote boot, PXE 2.1 support, Transmit Side Scaling (TSS), General Error Correction (GEC)

Compliant Standards	IEEE 802.2, IEEE 802.3z, IEEE 802.1Q, IEEE 802.1p, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.3ac, IEEE 802.3az
----------------------------	---

Expansion / Connectivity

Interfaces	1 x 1000Base-SX - ST - x 2
-------------------	----------------------------

Miscellaneous

Included Accessories	Full-height bracket
-----------------------------	---------------------

Compliant Standards	UL, TUV, VCCI, C-Tick, EN55024, EN55022 Class A, FCC, RoHS
----------------------------	--

Pricing Type	Federal government
---------------------	--------------------

Software / System Requirements

OS Required	Linux 2.6, Microsoft Windows Vista (32/64 bits), Microsoft Windows 7 (32/64 bits), Microsoft Windows XP (32/64 bits), Microsoft Windows Server 2008 (32/64-bits), Microsoft Windows Server 2003 (32/64-bits), Windows 8 (32/64 bits), Microsoft Windows Server 2008 R2 (32/64-bits), Microsoft Windows Server 2012 (32/64-bits), Microsoft Windows Server 2012 R2, Microsoft Windows Server 2012 R2 x64 Edition, Windows 10 (32/64 bits)
--------------------	--

Dimensions & Weight

Depth	8.8 cm
--------------	--------

Height	6.9 cm
---------------	--------

Weight	68 g
---------------	------

Environmental Parameters

Min Operating Temperature	0 °C
----------------------------------	------

Max Operating Temperature	40 °C
----------------------------------	-------

Humidity Range Operating	5 - 90% (non-condensing)
---------------------------------	--------------------------