

Produktinformation



Information

<i>Tillverkare</i>	Allied Telesis
<i>Artnr</i>	AT-2914SP-001

Allied Telesis AT-2914SP - Network adapter - PCIe low profile - 100Base-FX/1000Base-X x 1

Allied Telesis 2914 Series network adapters feature a PCI Express (PCIe x1) design, combining maximum bandwidth and PCI bus efficiency with the benefits of low power consumption. The 2914 is the Gigabit 1000SX fiber adapter with Wake-on-LAN (WoL) support completely through the PCI bus.

Specifikation

General

Device Type	Network adapter
Form Factor	Plug-in card - low profile
Interface (Bus) Type	PCI Express x1
Bus Voltage	3.3 V

Networking

Ports	100Base-FX/1000Base-X x 1
Connectivity Technology	Wired
Data Link Protocol	Gigabit Ethernet
Data Transfer Rate	1 Gbps
Remote Management Protocol	SNMP
Status Indicators	Link/activity
Features	VLAN support, Quality of Service (QoS), Jumbo Frames support, UEFI support, Link Aggregation Control Protocol (LACP), PXE 2.1 support, SNMP support
Compliant Standards	IEEE 802.2, IEEE 802.3z, IEEE 802.1Q, IEEE 802.1p, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1x, IEEE 802.3ac

Expansion / Connectivity

Interfaces	1 x 1000Base-X - SFP (mini-GBIC)
-------------------	----------------------------------

Miscellaneous

Included Accessories	Low-profile bracket, full-height bracket
Compliant Standards	UL, TUV, VCCI, C-Tick, EN55024, EN55022 Class A, RoHS

Software / System Requirements

OS Required	Linux, Microsoft Windows Vista / 7 / 8 / 10
--------------------	---

Dimensions & Weight

Width	8.8 cm
Height	6.9 cm
Weight	68 g

Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	50 °C
Humidity Range Operating	5 - 90% (non-condensing)