

Produktinformation



Information

<i>Tillverkare</i>	Allied Telesis
<i>Artnr</i>	AT-FS710/16-50

Allied Telesis CentreCOM AT-FS710/16 - Switch - unmanaged - 16 x 10/100 - desktop, rack-mountable

The Allied Telesis FS710 Series is the economical and eco-friendly solution for today's networks, providing an extensive range of cost-effective options.

Specifikation

General

Device Type	Switch - 16 ports - unmanaged
Enclosure Type	Desktop, rack-mountable
Subtype	Fast Ethernet
Ports	16 x 10/100
Performance	Switching capacity: 3.2 Gbps Throughput: 2.38 Mpps
MAC Address Table Size	8K entries
Features	Flow control, auto-negotiation, Jumbo Frames support, fanless, 256KB packet buffer, Bridge protocol data unit (BPDU)
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3az

Expansion / Connectivity

Interfaces	16 x 100Base-TX RJ-45
-------------------	-----------------------

Power

Power Device	Internal power supply
Voltage Required	AC 120/230 V (50 - 60 Hz)
Power Consumption Operational	4.5 Watt

Miscellaneous

Rack Mounting Kit	Included
--------------------------	----------

Compliant Standards	FCC Class A certified, UL 60950-1, EN 60950-1, FCC Part 15 B Class A, VCCI Class A, CSA 22.2 No. 60950-1, EN 55032 Class A, RCM Class A, CISPR 32 Class A, EU RoHS
Localisation	Europe
Dimensions & Weight	
Width	21 cm
Depth	12.4 cm
Height	4.4 cm
Weight	870 g
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	50 °C
Humidity Range Operating	5 - 90% (non-condensing)
Min Storage Temperature	-25 °C
Max Storage Temperature	70 °C
Humidity Range Storage	5 - 95% (non-condensing)