

Produktinformation



Information

<i>Tillverkare</i>	Allied Telesis
<i>Artnr</i>	AT-FS710/5-50

Allied Telesis AT FS710/5 - Switch - unmanaged - 5 x 10/100 - desktop, wall-mountable

The FS710/5 Unmanaged Fast Ethernet switch is an economical and eco-friendly solution, with 5 x 10/100TX ports and an internal PSU.

Specifikation

General

Device Type	Switch - 5 ports - unmanaged
Enclosure Type	Desktop, wall-mountable
Subtype	Fast Ethernet
Ports	5 x 10/100
Performance	Switching capacity: 1 Gbps Throughput: 0.74 Mpps
MAC Address Table Size	2K entries
Features	Flow control, auto-negotiation, Jumbo Frames support, fanless, 96KB packet buffer, Bridge protocol data unit (BPDU)
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3az
Status Indicators	Power, link/activity

Expansion / Connectivity

Interfaces	5 x 100Base-TX RJ-45
-------------------	----------------------

Power

Power Device	Internal power supply
Voltage Required	AC 120/230 V (50 - 60 Hz)
Power Consumption Operational	1.8 Watt

Miscellaneous

Compliant Standards	FCC Class B certified, UL 60950-1, EN 60950-1, VCCI Class B, CSA 22.2 No. 60950-1, EN 55032 Class A, CISPR 32 Class B, EU RoHS, RCM Class B
Localisation	Europe
Dimensions & Weight	
Width	13.1 cm
Depth	10.1 cm
Height	3 cm
Weight	400 g
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	50 °C
Humidity Range Operating	5 - 90% (non-condensing)
Min Storage Temperature	-25 °C
Max Storage Temperature	70 °C
Humidity Range Storage	5 - 95% (non-condensing)