

Produktinformation



Information

<i>Tillverkare</i>	Allied Telesis
<i>Artnr</i>	AT-FS750/20-50

Allied Telesis AT FS750/20 WebSmart - Switch - smart - 16 x 10/100 + 2 x 10/100/1000 + 2 x combo Gigabit SFP - desktop, rack-mountable

These advanced Allied Telesis WebSmart switches integrate the simplicity of unmanaged switches with the performance and reliability of managed switches to provide a cost-effective, yet secure and reliable, solution for users to integrate management at the edge of their networks. With user-friendly web-based management, the FS750 Series is an ideal option for integrating simple management and security into a network solution.

Specifikation

General

Device Type	Switch - 16 ports - smart
Enclosure Type	Desktop, rack-mountable 1U
Subtype	Fast Ethernet
Ports	16 x 10/100 + 2 x 10/100/1000 + 2 x combo Gigabit SFP
MAC Address Table Size	8000 entries
Jumbo Frame Support	10KB
Remote Management Protocol	SNMP 1, RMON 1, RMON 2, RMON 3, RMON 9, SNMP 3, SNMP 2c, HTTP
Encryption Algorithm	MD5
Authentication Method	RADIUS
Features	Flow control, trunking, auto-uplink (auto MDI/MDI-X), IGMP snooping, Syslog support, port mirroring, Broadcast Storm Control, STNP support, Spanning Tree Protocol (STP) support, Rapid Spanning Tree Protocol (RSTP) support, Multiple Spanning Tree Protocol (MSTP) support, DHCP snooping, Access Control List (ACL) support, RADIUS support, LLDP support, Link Aggregation Control Protocol (LACP), DHCP client, tagged VLAN
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s

RAM	128 MB
Flash Memory	16 MB
Status Indicators	Port transmission speed, power, link/activity
Expansion / Connectivity	
Interfaces	16 x 100Base-TX RJ-45 4 x 1000Base-T RJ-45 2 x SFP
Power	
Power Device	Internal power supply
Voltage Required	AC 120/230 V (50/60 Hz)
Miscellaneous	
Rack Mounting Kit	Included
MTBF	263,000 hours
Compliant Standards	FCC Class A certified, CSA, UL, TUV, C-Tick, cUL, EN 60950, EN55024, EN55022 Class A, RoHS, UL 94 V-0, UL 60950-1 Second Edition, WEEE, IEC 60068-2-32, IEC 60068-2-29, VCCI Class A, China RoHS
Localisation	Europe
Dimensions & Weight	
Width	33 cm
Depth	18 cm
Height	4.4 cm
Weight	1.4 kg
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	5 - 90% (non-condensing)
Min Storage Temperature	-25 °C
Max Storage Temperature	70 °C
Humidity Range Storage	5 - 95% (non-condensing)