

Produktinformation



Information

<i>Tillverkare</i>	Allied Telesis
<i>Artnr</i>	AT-FS750/28PS-50

Allied Telesis AT FS750/28PS WebSmart - Switch - Managed - 20 x 10/100 (PoE) + 2 x combo Gigabit SFP + 2 x 10/100/1000 + 4 x 10/100 (PoE+) - desktop, rack-mountable, wall-mountable - PoE+ (193 W)

The Allied Telesis AT-FS750/28PS WebSmart network switch features PoE+ for connectivity with security cameras, VoIP phones, RFID readers, and wireless access points. The FS750PS series is a cost effective solution for SMB, retail stores, and at the edge of the network.

Specifikation

General

Device Type	Switch - 28 ports - Managed
Enclosure Type	Desktop, rack-mountable, wall-mountable 1U
Subtype	Fast Ethernet
Ports	20 x 10/100 (PoE) + 2 x combo Gigabit SFP + 2 x 10/100/1000 + 4 x 10/100 (PoE+)
Power Over Ethernet (PoE)	PoE+
PoE Budget	193 W
Capacity	VLANs supported: 256 ACL entries: 20
MAC Address Table Size	8000 entries
Jumbo Frame Support	10KB
Remote Management Protocol	SNMP 1, RMON 1, RMON 2, RMON 3, RMON 9, SNMP 3, SNMP 2c, HTTP
Encryption Algorithm	MD5
Authentication Method	RADIUS
Features	Flow control, Syslog support, port mirroring, MAC address filtering, Broadcast Storm Control, Spanning Tree Protocol (STP) support, Rapid Spanning Tree Protocol (RSTP) support, Multiple Spanning Tree

Compliant Standards	Protocol (MSTP) support, DHCP snooping, RADIUS support, fanless, LLDP support, Link Aggregation Control Protocol (LACP), DHCP client IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s
RAM	128 MB
Flash Memory	16 MB
Expansion / Connectivity	
Interfaces	24 x 100Base-TX RJ-45 4 ports (PoE+) / 20 ports (PoE) - 193 W 2 x 1000Base-T RJ-45 12 x 100Base-TX RJ-45 2 x 1000Base-T SFP
Power	
Power Device	Internal power supply
Voltage Required	AC 120/230 V (50/60 Hz)
Miscellaneous	
Rack Mounting Kit	Included
MTBF	263,000 hours
Compliant Standards	FCC Class A certified, CSA, TUV, C-Tick, CISPR 22 Class A, EN 60950, EN55024, RoHS, UL 94 V-0, UL 60950-1 Second Edition, WEEE, IEC 60068-2-32, IEC 60068-2-29, VCCI Class A, China RoHS, EN 55022 Class A
Localisation	Europe
Dimensions & Weight	
Width	44 cm
Depth	25 cm
Height	4.4 cm
Weight	3.2 kg
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	5 - 90% (non-condensing)
Min Storage Temperature	-25 °C
Max Storage Temperature	70 °C
Humidity Range Storage	5 - 95% (non-condensing)