

## Produktinformation



### Information

<i>Tillverkare</i>	Allied Telesis
<i>Artnr</i>	AT-FS750/28-50

## Allied Telesis AT FS750/28 WebSmart - Switch - smart - 24 x 10/100 + 2 x 10/100/1000 + 2 x combo Gigabit SFP - desktop, rack-mountable

These advanced Allied Telesis WebSmart switches integrate the simplicity of unmanaged switches with the performance and reliability of managed switches to provide a cost-effective, yet secure and reliable, solution for users to integrate management at the edge of their networks. With user-friendly web-based management, the FS750 series is an ideal possibility for integrating simple management and security into a network solution.

## Specifikation

### General

<b>Device Type</b>	Switch - 24 ports - smart
<b>Enclosure Type</b>	Desktop, rack-mountable 1U
<b>Subtype</b>	Fast Ethernet
<b>Ports</b>	24 x 10/100 + 2 x 10/100/1000 + 2 x combo Gigabit SFP
<b>MAC Address Table Size</b>	8000 entries
<b>Jumbo Frame Support</b>	10KB
<b>Remote Management Protocol</b>	SNMP 1, RMON 1, RMON 2, RMON 3, RMON 9, SNMP 3, SNMP 2c, HTTP
<b>Encryption Algorithm</b>	MD5
<b>Authentication Method</b>	RADIUS
<b>Features</b>	Flow control, trunking, auto-uplink (auto MDI/MDI-X), IGMP snooping, Syslog support, port mirroring, Broadcast Storm Control, STNP support, Spanning Tree Protocol (STP) support, Rapid Spanning Tree Protocol (RSTP) support, Multiple Spanning Tree Protocol (MSTP) support, DHCP snooping, Access Control List (ACL) support, RADIUS support, LLDP support, Link Aggregation Control Protocol (LACP), DHCP client, tagged VLAN
<b>Compliant Standards</b>	IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s

<b>RAM</b>	128 MB
<b>Flash Memory</b>	16 MB
<b>Status Indicators</b>	Port transmission speed, power, link/activity
Expansion / Connectivity	
<b>Interfaces</b>	24 x 100Base-TX RJ-45 4 x 1000Base-T RJ-45 2 x SFP
Power	
<b>Power Device</b>	Internal power supply
<b>Voltage Required</b>	AC 120/230 V (50/60 Hz)
Miscellaneous	
<b>Rack Mounting Kit</b>	Included
<b>MTBF</b>	263,000 hours
<b>Compliant Standards</b>	FCC Class A certified, CSA, UL, TUV, C-Tick, cUL, EN 60950, EN55024, EN55022 Class A, RoHS, UL 94 V-0, UL 60950-1 Second Edition, WEEE, IEC 60068-2-32, IEC 60068-2-29, VCCI Class A, China RoHS
<b>Localisation</b>	Europe
Dimensions & Weight	
<b>Width</b>	33 cm
<b>Depth</b>	18 cm
<b>Height</b>	4.4 cm
<b>Weight</b>	2 kg
Environmental Parameters	
<b>Min Operating Temperature</b>	0 °C
<b>Max Operating Temperature</b>	40 °C
<b>Humidity Range Operating</b>	5 - 90% (non-condensing)
<b>Min Storage Temperature</b>	-25 °C
<b>Max Storage Temperature</b>	70 °C
<b>Humidity Range Storage</b>	5 - 95% (non-condensing)