

Produktinformation



Information

<i>Tillverkare</i>	Allied Telesis
<i>Artnr</i>	AT-GS910/24-50

Allied Telesis AT GS910/24 - Switch - unmanaged - 24 x 10/100/1000 - rack-mountable

Specifikation

General

Device Type	Switch - 24 ports - unmanaged
Enclosure Type	Rack-mountable 1U
Subtype	Gigabit Ethernet
Ports	24 x 10/100/1000
MAC Address Table Size	16K entries
Features	Auto-uplink (auto MDI/MDI-X), fanless
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.3ab, IEEE 802.3x

Expansion / Connectivity

Interfaces	24 x 1000Base-T RJ-45
-------------------	-----------------------

Power

Power Device	Internal power supply
---------------------	-----------------------

Miscellaneous

Compliant Standards	FCC Class A certified, TUV, C-Tick, EN 60950, UL 1950, EN55024, EN55022 Class A, VCCI Class A
Localisation	Europe

Dimensions & Weight

Width	28 cm
Depth	18 cm
Height	4.4 cm
Weight	1.79 kg

Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	5 - 90% (non-condensing)
Min Storage Temperature	-25 °C
Max Storage Temperature	70 °C
Humidity Range Storage	5 - 95% (non-condensing)