

## Produktinformation



### Information

<i>Tillverkare</i>	Allied Telesis
<i>Artnr</i>	AT-GS950/24-50

## Allied Telesis AT GS950/24 WebSmart Switch - Switch - Managed - 24 x 10/100/1000 + 2 x GBIC - desktop

Allied Telesis' GS950 Series WebSmart Switch integrates the simplicity of unmanaged switches with the performance and reliability of managed switches to provide a cost-effective solution integrating management at the edge of the network. WebSmart switch provides key features using simple web-based management, such as: port-based VLANs, 802.1p QoS, port trunking/link aggregation, port mirroring, priority queue's, spanning tree & 802.1x security support. With up to 8K MAC addresses & a 512K packet buffer, the GS950 Series WebSmart switch is an ideal option for integrating management into your network solution.

## Specifikation

### General

<b>Device Type</b>	Switch - 24 ports - Managed
<b>Enclosure Type</b>	Desktop
<b>Subtype</b>	Gigabit Ethernet
<b>Ports</b>	24 x 10/100/1000 + 2 x GBIC
<b>MAC Address Table Size</b>	8K entries
<b>Remote Management Protocol</b>	HTTP
<b>Features</b>	Flow control, trunking, auto-uplink (auto MDI/MDI-X), port mirroring
<b>Compliant Standards</b>	IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.1x
<b>RAM</b>	512 KB

### Expansion / Connectivity

<b>Interfaces</b>	24 x 1000Base-T RJ-45 1 x serial (RS-232) DB-9 management 2 x GBIC
-------------------	--

### Power

<b>Power Device</b>	Internal power supply
<b>Voltage Required</b>	AC 120/230 V (50/60 Hz)

Miscellaneous	
Mounting Kit	Included
Rack Mounting Kit	Included
Compliant Standards	FCC Class A certified, TUV, C-Tick, EN 60950, UL 1950, VCCI Class A ITE, EN55024, EN55022 Class A
Localisation	Europe
Dimensions & Weight	
Width	44 cm
Depth	25.7 cm
Height	4.3 cm
Manufacturer Warranty	
Service & Support	Limited warranty - lifetime
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	5 - 90%