

Produktinformation



Information

<i>Tillverkare</i>	Allied Telesis
<i>Artnr</i>	AT-GS950/8-50

Allied Telesis AT GS950/8 WebSmart Switch - Switch - Managed - 8 x 10/100/1000 + 2 x shared SFP - desktop

Allied Telesis' WebSmart switch integrates the simplicity of unmanaged switches with the performance and reliability of managed switches to provide a cost-effective solution for users to integrate management at the edge of their network. This WebSmart switch provides a network manager some key features using the simple web-based management function such as: port based Vlans, 802.1p QoS, port trunking/link aggregation, port mirroring, priority queue's & 802.1x security support. With support of up to 4K MAC addresses & a 128K packet buffer GS950/8 WebSmart switch is an ideal option for integrating management into your network solution. Never thought you could afford managed switches in your network? Always wanted to provide management functionality at the edge? Allied Telesis' WebSmart switch truly helps network managers get the most value for their dollar. With industry standard protocols, fiber media support via the SFPs and simple plug and play usability right out of the box how can you go wrong implementing this cost-effective solution into your network?

Specifikation

General

Device Type	Switch - 8 ports - Managed
Enclosure Type	Desktop 1U
Subtype	Gigabit Ethernet
Ports	8 x 10/100/1000 + 2 x shared SFP
MAC Address Table Size	4K entries
Remote Management Protocol	HTTP
Features	Flow control, auto-sensing per device, auto-negotiation, trunking, VLAN support, port mirroring, wall mountable
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.1D, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1x
Status Indicators	Port transmission speed, port duplex mode, power, link OK, link/activity

Expansion / Connectivity

Interfaces	8 x 1000Base-T RJ-45 1 x console RJ-45 management 2 x SFP (mini-GBIC)
-------------------	---

Power	
Power Device	Internal power supply
Voltage Required	AC 120/230 V (50/60 Hz)
Miscellaneous	
Mounting Kit	Included
Rack Mounting Kit	Included
Compliant Standards	FCC Class A certified, TUV, C-Tick, EN 60950, UL 1950, VCCI Class A ITE, EN55024, EN55022 Class A, RoHS
Localisation	Europe
Dimensions & Weight	
Width	28 cm
Depth	17.7 cm
Height	4.4 cm
Manufacturer Warranty	
Service & Support	Limited warranty - lifetime
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	5 - 90%