

Produktinformation



Information

<i>Tillverkare</i>	Allied Telesis
<i>Artnr</i>	AT-IMC2000TP/SP-980

Allied Telesis Industrial Ethernet Media Converter AT-IMC2000TP/SP - Fibre media converter - GigE - 10Base-T, 100Base-TX, 1000Base-T, 1000Base-X, 100Base-X - RJ-45

Allied Telesis Industrial Ethernet Media Converter offers an operating range from -40 °C to 75 °C. The temperature-hardened IMC series features Plug and Play and auto-negotiation.

Specifikation

General

Device Type	Fibre media converter
Form Factor	External

Networking

Connectivity Technology	Wired
Cabling Type	10Base-T, 100Base-TX, 1000Base-T, 1000Base-X, 100Base-X
Data Link Protocol	100Mb LAN, GigE
Data Transfer Rate	1 Gbps
Status Indicators	Link/activity
Compliant Standards	IEEE 802.3at

Expansion / Connectivity

Interfaces	1 x Ethernet 1000Base-X - SFP female 1 x Ethernet 1000Base-T (PoE) - RJ-45 female
-------------------	---

Miscellaneous

Compliant Standards	FCC Class A certified, VCCI, EN55024, ICES, EN61000-3-2, EN61000-3-3, EN 55032
----------------------------	--

Power

Power Over Ethernet (PoE)	PoE+
----------------------------------	------

Dimensions & Weight

Width	11.1 cm
Depth	9.6 cm
Height	3.5 cm
Weight	748 g

Environmental Parameters

Min Operating Temperature	-40 °C
Max Operating Temperature	75 °C
Humidity Range Operating	5 - 90% (non-condensing)