

Produktinformation



Information

<i>Tillverkare</i>	Allied Telesis
<i>Artnr</i>	AT-MMC2000/SC-960

Allied Telesis AT-MMC2000/SC - Fibre media converter - GigE - 10Base-T, 1000Base-SX, 100Base-TX, 1000Base-T - RJ-45 / SC multi-mode - up to 500 m - 850 nm - TAA Compliant

The Allied Telesis MMC2000 Series of Gigabit mini media converters leverages its smaller size to not only help the environment with a small carbon footprint, but also to save space in its working environment. Despite its compact size, the MMC2000 Series delivers all the power and functionality of standard size media converters.

Specifikation

General

Device Type	Fibre media converter
Form Factor	External

Networking

Connectivity Technology	Wired
Cabling Type	10Base-T, 1000Base-SX, 100Base-TX, 1000Base-T
Data Link Protocol	GigE
Data Transfer Rate	1 Gbps
Optical Wave Length	850 nm
MAC Address Table Size	2K entries
Max Transfer Distance	500 m
Status Indicators	Power, system, link/activity
Features	Auto-negotiation, VLAN support, auto-uplink (auto MDI/MDI-X), Smart Missing Link (SML), store and forward, Jumbo Frames support
Compliant Standards	IEEE 802.1Q

Expansion / Connectivity

Interfaces	1 x Ethernet 1000Base-SX - SC multi-mode female x 2 1 x Ethernet 10Base-T/100Base-TX/1000Base-T - RJ-45 female
-------------------	--

Miscellaneous

Compliant Standards	FCC Class A certified, VCCI, C-Tick, CISPR 22, UL 60950-1, EN 60950-1, EN 55022 Class A
TAA Compliant	Yes

Power

Power Consumption Operational	1.7 Watt
--------------------------------------	----------

Dimensions & Weight

Width	5.49 cm
Depth	10.16 cm
Height	2.18 cm
Weight	170 g

Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	50 °C
Humidity Range Operating	5 - 95% (non-condensing)