

Produktinformation



Information

<i>Tillverkare</i>	Allied Telesis
<i>Artnr</i>	AT-MMC200/LC-960

Allied Telesis AT MMC200/LC - Fibre media converter - 100Mb LAN - 10Base-T, 100Base-FX, 100Base-TX - RJ-45 / LC multi-mode - up to 2 km - 1310 nm - TAA Compliant

The Allied Telesis MMC200 series of Fast Ethernet mini media converters leverages its smaller size to not only help the environment with a small carbon footprint, but also to save space in its working environment. Despite its compact size, the MMC200 series delivers all the power and functionality of standard size media converters.

Specifikation

General

Device Type	Fibre media converter
Form Factor	External

Networking

Connectivity Technology	Wired
Cabling Type	10Base-T, 100Base-FX, 100Base-TX
Data Link Protocol	100Mb LAN
Data Transfer Rate	100 Mbps
Optical Wave Length	1310 nm
MAC Address Table Size	2K entries
Max Transfer Distance	2 km
Status Indicators	Power, system, link/activity
Features	Full duplex capability, auto-negotiation, VLAN support, auto-uplink (auto MDI/MDI-X), Smart Missing Link (SML), store and forward, wall mountable, Jumbo Frames support, Energy Efficient Ethernet, Automatic Link Restoration
Compliant Standards	IEEE 802.1Q

Expansion / Connectivity

Interfaces	1 x Ethernet 100Base-FX - LC multi-mode female x 2 1 x Ethernet 10Base-T/100Base-TX - RJ-45 female
Miscellaneous	
Compliant Standards	FCC Class A certified, VCCI, C-Tick, CISPR 22 Class A, EN 61000-3-2, EN 61000-3-3, EN55024, UL 60950-1, EN 60950-1, EN 55022 Class A
TAA Compliant	Yes
Power	
Power Device	External power adapter
Power Consumption Operational	1.7 Watt
Dimensions & Weight	
Width	5.6 cm
Depth	10.16 cm
Height	2.18 cm
Weight	170 g
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	50 °C
Humidity Range Operating	5 - 95% (non-condensing)