

Produktinformation



Information

<i>Tillverkare</i>	Allied Telesis
<i>Artnr</i>	AT-MMC6005-60

Allied Telesis AT MMC6005 - Network extender - GigE, Ethernet over VDSL2 - 10Base-T, 100Base-TX, 1000Base-T - up to 3 km

Used as a pair, the Allied Telesis AT-MMC6005 provides bidirectional data transfer. These units are the ideal solution for providing data on last-mile twisted-pair circuits or existing in-building wiring. Standard Ethernet operation is preserved end-to-end, retaining VLAN tags, and Ethernet MAC information across the link, while higher layer protocols are passed transparently.

Specifikation

General

Device Type	Network extender
Form Factor	External
Localisation	Europe

Networking

Connectivity Technology	Wired
Cabling Type	10Base-T, 100Base-TX, 1000Base-T
Data Link Protocol	10Mb LAN, 100Mb LAN, GigE, Ethernet over VDSL2
Data Transfer Rate	150 Mbps
Max Transfer Distance	3 km
Status Indicators	Power, link/activity
Features	Auto-negotiation, auto-uplink (auto MDI/MDI-X), half duplex mode, full duplex mode, wall mountable, metal housing

Expansion / Connectivity

Interfaces	1 x Ethernet 10Base-T/100Base-TX/1000Base-T - RJ-45 1 x network - RJ-11 1 x modem - RJ-11
-------------------	---

Miscellaneous

Compliant Standards	CSA, TUV, EN 60950, UL 1950, EN50082-1, EN55022 Class B
----------------------------	---

Power

Power Device	External power adapter
Voltage Required	AC 230V
Power Consumption Operational	2 Watt

Dimensions & Weight

Width	5.08 cm
Depth	9.91 cm
Height	2.03 cm
Weight	200 g

Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	50 °C
Humidity Range Operating	5 - 90% (non-condensing)