

## Produktinformation



### Information

<i>Tillverkare</i>	Allied Telesis
<i>Artnr</i>	AT-PC2000/LC-60

## Allied Telesis AT-PC2000/LC - Fibre media converter - GigE - 10Base-T, 1000Base-LX, 1000Base-SX, 100Base-TX, 1000Base-T - SFP (mini-GBIC) / RJ-45 - 850 nm

Allied Telesis PC2000 series media converters are the ideal solution for powering remote devices such as IP phones, video cameras, wireless access points, etc.

## Specifikation

### General

<b>Device Type</b>	Fibre media converter
<b>Form Factor</b>	Wall mountable

### Networking

<b>Connectivity Technology</b>	Wired
<b>Cabling Type</b>	10Base-T, 1000Base-LX, 1000Base-SX, 100Base-TX, 1000Base-T
<b>Data Link Protocol</b>	10Mb LAN, 100Mb LAN, GigE
<b>Data Transfer Rate</b>	1 Gbps
<b>Optical Wave Length</b>	850 nm
<b>MAC Address Table Size</b>	4K entries
<b>Status Indicators</b>	Power, active, fault
<b>Features</b>	VLAN support, auto-uplink (auto MDI/MDI-X), Smart Missing Link (SML), store and forward, Jumbo Frames support
<b>Compliant Standards</b>	IEEE 802.1Q, IEEE 802.3at

### Expansion / Connectivity

<b>Interfaces</b>	1 x Ethernet 10Base-T/100Base-TX/1000Base-T - RJ-45 female 1 x Ethernet 1000Base-LX/1000Base-SX - LC female x 2
-------------------	---

### Miscellaneous

<b>Compliant Standards</b>	FCC Class B certified, C-Tick, EN55022 Class A
----------------------------	--

Power

<b>Power Over Ethernet (PoE)</b>	PoE+
<b>Power Device</b>	Internal power supply
<b>Installed Qty</b>	1
<b>Max Supported Qty</b>	1
<b>Voltage Required</b>	AC 120/230 V (50/60 Hz)
<b>Power Consumption Operational</b>	35 Watt

Dimensions & Weight

<b>Width</b>	15.5 cm
<b>Depth</b>	14.9 cm
<b>Height</b>	4 cm
<b>Weight</b>	748 g

Environmental Parameters

<b>Min Operating Temperature</b>	0 °C
<b>Max Operating Temperature</b>	50 °C
<b>Humidity Range Operating</b>	5 - 95% (non-condensing)