

Produktinformation



Information

<i>Tillverkare</i>	Allied Telesis
<i>Artnr</i>	AT-PC2000/SP-60

Allied Telesis AT-PC2000/SP - Fibre media converter - GigE - 10Base-T, 100Base-TX, 1000Base-T, 1000Base-X, 100Base-X - SFP (mini-GBIC) / RJ-45 - 850 nm

Allied Telesis PC2000 Series media converters are the ideal solution for powering remote devices such as IP phones, video cameras, wireless access points, etc.

Specifikation

General

Device Type	Fibre media converter
Form Factor	Wall mountable

Networking

Connectivity Technology	Wired
Cabling Type	10Base-T, 100Base-TX, 1000Base-T, 1000Base-X, 100Base-X
Data Link Protocol	10Mb LAN, 100Mb LAN, GigE
Data Transfer Rate	1 Gbps
Optical Wave Length	850 nm
MAC Address Table Size	4K entries
Status Indicators	Power, active, fault
Features	VLAN support, auto-uplink (auto MDI/MDI-X), Smart Missing Link (SML), store and forward, Jumbo Frames support
Compliant Standards	IEEE 802.1Q, IEEE 802.3at

Expansion / Connectivity

Interfaces	1 x Ethernet 10Base-T/100Base-TX/1000Base-T - RJ-45 female 1 x Ethernet 100Base-X/1000Base-X - SFP female
-------------------	---

Miscellaneous

Compliant Standards	FCC Class B certified, C-Tick, EN55022 Class A
----------------------------	--

Power

Power Over Ethernet (PoE)	PoE+
Power Device	Internal power supply
Installed Qty	1
Max Supported Qty	1
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	35 Watt

Dimensions & Weight

Width	15.5 cm
Depth	14.9 cm
Height	4 cm
Weight	748 g

Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	50 °C
Humidity Range Operating	5 - 95% (non-condensing)