

## Produktinformation



### Apple AirPort Extreme Base Station - Radio access point - Wi-Fi - 2.4 GHz, 5 GHz - for Apple TV (2nd,3rd,4th Generation)

#### Information



<i>Tillverkare</i>	Apple
<i>Artnr</i>	ME918Z/A-REF

With three-stream 802.11ac technology, the AirPort Extreme Base Station takes Wi-Fi speeds over the top. You can reach data rates of up to 1.3 Gbps - triple the previous 802.11n standard. Which means up to three times faster Wi-Fi. 2 You also get double the channel bandwidth, with 80 MHz-wide channels providing more room for more data to flow faster than ever. And if you have 802.11 a/b/g/n devices, AirPort Extreme maximizes that connection as well. What you do with all that extra speed is up to you. AirPort Extreme features simultaneous dual-band 802.11ac Wi-Fi. That means it transmits at both the 2.4 GHz and 5 GHz frequencies at the same time. So no matter which band your wireless devices use, they will automatically connect to the best available band for the fastest possible performance.

## Specifikation

### General

<b>Status</b>	R4
<b>Device Type</b>	Radio access point
<b>Built-in Devices</b>	Print server
<b>Width</b>	9.8 cm
<b>Depth</b>	9.8 cm
<b>Height</b>	16.8 cm
<b>Weight</b>	0.945 kg

### Networking

<b>Form Factor</b>	External
<b>Connectivity Technology</b>	Wireless
<b>Data Link Protocol</b>	IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac (draft 2.0)
<b>Network / Transport Protocol</b>	PPTP, L2TP, IPSec, PPPoE, DHCP, Bonjour
<b>Frequency Band</b>	2.4 GHz, 5 GHz
<b>Capacity</b>	Connection / user qty: 50
<b>Status Indicators</b>	Status

<b>Features</b>	DHCP support, NAT support, MAC address filtering, IPv6 support, VPN passthrough
<b>Encryption Algorithm</b>	LEAP, TLS, PEAP, TTLS, WPA, WPA2, WPA-Enterprise, WPA2-Enterprise
<b>Authentication Method</b>	EAP-FAST
<b>Compliant Standards</b>	IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.1x, IEEE 802.11n, IEEE 802.11ac (draft 2.0)
Aerial	
<b>Antenna</b>	Internal
Expansion / Connectivity	
<b>Interfaces</b>	1 x USB - Type A 1 x 100Base-TX - RJ-45 (WAN) 3 x 100Base-TX - RJ-45
Miscellaneous	
<b>Compliant Standards</b>	UL 60950, CSA 22.2 No. 60950, FCC Part 15 B, RSS-210, AS/NZS 4268, ARIB STD-T66, RCR STD-33, GB 4943, EN 300 328, EN 301 893
Power	
<b>Power Device</b>	Internal power supply
<b>Voltage Required</b>	AC 120/230 V (50/60 Hz)
Software / System Requirements	
<b>OS Required</b>	Apple MacOS X 10.2.7 or later, Microsoft Windows Vista SP2, Microsoft Windows XP SP3, Microsoft Windows 7 SP1, Windows 8
Environmental Parameters	
<b>Min Operating Temperature</b>	0 °C
<b>Max Operating Temperature</b>	35 °C
<b>Humidity Range Operating</b>	20 - 80% (non-condensing)
Compatibility Information	
<b>Designed For</b>	Apple TV (2nd,3rd,4th Generation)