

Produktinformation



Information

<i>Tillverkare</i>	Avocor
<i>Artnr</i>	AVE-8610

Avocor E8610 - 86" Diagonal Class E-Series LED display - interactive digital signage - with touchscreen (multi touch) - 4K UHD (2160p) 3840 x 2160 - direct-lit LED

The E8610 integrates optically bonded glass into a 4K interactive display, producing a visually stunning interactive experience. Collaboration is incredibly natural with multiple touch points, while users will enjoy the superior writing and inking performance from the fine-tip passive pen and object recognition which easily identifies between pen, finger and palm for a smooth transition experience. Optimized for Windows 10, the E8610 includes edge swipe functionality, while the anti-glare and anti-fingerprint glass provides a smooth surface that is just like using a giant tablet.

Specifikation

General

Product Type	LED-backlit LCD flat panel display
Power Consumption Operational	450 Watt
Diagonal Class	86"
Commercial Use	Yes - interactive digital signage
Combined With	Touchscreen (multi touch)
Series	E-Series
TV Tuner Presence	No
Video Interface	HDMI
HDMI Ports Qty	4 ports
PC Interface	DisplayPort
Modes	Landscape mode
Picture Enhancements	30-bit Deep Colour
Width	201.8 cm
Depth	10.4 cm
Height	121.1 cm

Weight	65 kg
Display	
Resolution	3840 x 2160
Display Format	4K UHD (2160p)
Image Aspect Ratio	16:9
Frame Rate & Enhancement Technology	60 Hz Refresh Rate
LCD Backlight Technology	LED backlight
Coating	Anti-glare
Image Contrast Ratio	4000:1
Brightness	370 cd/m²
Viewing Angle	178 degrees
Viewing Angle (Vertical)	178 degrees
Touchpoints Qty	20
Response Time	8 ms
Commercial Features	Open Pluggable Standard (OPS) support
Features	Optical bonding, anti-fingerprint, Avocor Intelligent Touch
Stands & Mounts	
Flat Panel Mount Interface	800 x 400 mm
VESA Compatibility	Yes
Media Player	
USB Port	Yes
USB Ports Qty	3
Remote Control	
Type	Remote control
Audio System	
Speaker System	2 speakers
Output Power / Total	30 Watt
Speakers	2 x main channel speaker - 15 Watt
Connections	
Connector Type	4 x HDMI input DisplayPort HDMI output Audio line-out 2 x touch in 3 x USB 2.0 2 x LAN SPDIF output RS-232
Miscellaneous	
Included Accessories	Stylus, batteries
Cables Included	2 x USB cable - 3 m 2 x HDMI cable - 3 m 2 x USB-A to USB-B adapter
Power	
Power Device	Power supply

Nominal Voltage AC 120/230 V (50/60 Hz)

Power Consumption Stand by 0.5 Watt

Manufacturer Warranty

Service & Support Limited warranty - 3 years

Dimensions & Weight (Shipping)

Width (Shipping) 218 cm

Depth (Shipping) 34 cm

Height (Shipping) 134 cm

Weight (Shipping) 87 kg

Environmental Parameters

Min Operating Temperature 0 °C

Max Operating Temperature 40 °C

Humidity Range Operating 20 - 80%