

Produktinformation



Information

<i>Tillverkare</i>	Axis Communications
<i>Artnr</i>	01025-001

AXIS C8033 Network Audio Bridge - Audio extender

Axis C8033 network audio bridge is a smart solution for connecting and combining analog and digital audio systems. With this scalable and cost-efficient product, you can connect analog audio sources to Axis network speaker system, connect digital audio sources to an analog speaker system, or combine analog and digital speaker systems to act as one. Based on open standards, the audio bridge is easily integrated with other systems. It is small, easy to place, and easy to connect, using Power over Ethernet.

Specifikation

General

Device Type	Audio extender
Form Factor	External
Built-in Devices	microSD card reader, SDHC card reader, SDXC card reader, 256 MB RAM, 512 MB flash
Colour	Black

Networking

Connectivity Technology	Wired
Framing Format	G.711
Remote Management Protocol	SNMP 1, SNMP 3, SNMP 2c, HTTP, HTTPS, SSH, SFTP, SMTP
Features	DHCP support, ARP support, DiffServ support, E-mail alert, IPv6 support, IP address filtering, two-way audio support, Quality of Service (QoS), IPv4 support, Network Access Control (NAC), 802.1x authentication, administrator's password, Internet Control Message Protocol (ICMP), Management Information Base (MIB) II, Network Timing Protocol (NTP)
Compliant Standards	IEEE 802.3af, IEEE 802.1x, G.726

Expansion / Connectivity

Interfaces	1 x audio - RCA x 2 female 1 x - terminal block x 4
-------------------	---

Miscellaneous

Compliant Standards	EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, ICES-003 Class A, UL 2043, EN 61000-6-2, IEC 60068-2-27, IEC 60068-2-6, FCC Part 15 B Class A, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IP20, VCCI Class A, IEC EN60529, AS/NZS CISPR 32 Class A, EN 62368-1, IEC 62368-1, EN 55032 Class A, UL 62368-1, EN 55035, NEMA250 Type 1
Power	
Power Device	External power adapter
Dimensions & Weight	
Width	5.7 cm
Depth	12.9 cm
Height	2.4 cm
Weight	102 g
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years
Environmental Parameters	
Min Operating Temperature	-20 °C
Max Operating Temperature	50 °C