

Produktinformation



Information

<i>Tillverkare</i>	Axis Communications
<i>Artnr</i>	01916-001

Axis C1410 Network Mini Speaker - IP speaker - for PA system - Ethernet, Fast Ethernet, PoE - 7 Watt - white

Deter unwanted activity and warn off bad actors detected by your cameras with AXIS C1410 Network Mini Speaker. You can also use voice messages to provide instructions when needed. Smart and easy-to-integrate, AXIS C1410 is designed to fit discreetly into smaller spaces.

Specifikation

General

Product Type	IP speaker - for PA system
Features	DSP
Microphone	Yes
Sensors	Motion sensor
Enclosure Colour	White
Localisation	English, German, French, Italian, Spanish

Speaker System

Speaker Type	Active
Nominal Output Power	7 Watt
Frequency Response	100 - 20000 Hz
Max Output Level (Max SPL)	90 dB
Amplifier	Integrated
Coverage	145°
Interfaces	IEEE 802.3 (Ethernet), IEEE 802.3u (Fast Ethernet), IEEE 802.3af (Power over Ethernet)
VoIP Protocols	SRTP, SIP over TLS, SIPS
Voice Codecs	Speex, Opus, L16, PCMA, PCMU, G.726-32
Network Protocols	TCP, UDP, ICMP, ARP, HTTP, DNS, SNMP, HTTPS, NTP

Audio Formats WAV, PCM, G.726, MP3, ADPCM, AAC-LC, G.711

Speaker System Details

Driver Details Speaker: - 2.5"

Connections

Connector Type LAN (RJ-45)

Miscellaneous

Included Accessories AVHS authentication key, AXIS Camera Station licence key

Compliant Standards EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, FCC Part 15 B, EN 61000-6-2, IP40, VCCI Class B, EN 55032 Class B, AS/NZS CISPR 32 Class B, EN 55035, IEC/EN/UL 62368-1, CAN ICES-3(B)/NMB3(B)

Power

Power Source Power over Ethernet (PoE)

Dimensions & Weight

Width 18.2 cm

Depth 18.2 cm

Height 5.2 cm

Weight 600 g

Manufacturer Warranty

Service & Support Limited warranty - 3 years