

## Produktinformation



### Information

<i>Tillverkare</i>	Axis Communications
<i>Artnr</i>	02079-002

## AXIS Camera Station S1132 Recorder - tower - Core i3 - 16 GB - HDD 4 x 8 TB

AXIS Camera Station S1132 Recorder is an out-of-the-box, ready-to-use recording solution designed to deliver reliable high-definition surveillance. The recorder is available as a rack server for server room installation, with a large storage capacity. From manufacturing facilities to schools and retail, AXIS Camera Station S1132 Recorder meets the requirements of a wide variety of businesses and industries. It's ideal whenever reliable and secure surveillance is required.

## Specifikation

### General

<b>Type</b>	Server
<b>Product Form Factor</b>	Tower
<b>Hot-Swap Bays Qty</b>	8
<b>Localisation</b>	Region: Europe

### Processor / Chipset

<b>CPU</b>	Intel Core i3
<b>CPU Qty</b>	1

### RAM

<b>Installed Size</b>	16 GB
<b>Configuration Features</b>	2 x 8 GB

### Hard Drive

<b>Type</b>	HDD - hot-swap
<b>Capacity</b>	4 x 8 TB
<b>Features</b>	RAID 5 - factory configured, Enterprise

### Storage Controller

<b>Type</b>	RAID
<b>RAID Level</b>	RAID 0, RAID 1, RAID 5, RAID 6, RAID 10, JBOD

Monitor	
<b>Monitor Type</b>	None.
Graphics Controller	
<b>Graphics Processor</b>	NVIDIA Quadro
Networking	
<b>Ethernet Ports</b>	2 x Gigabit Ethernet
<b>Data Link Protocol</b>	Ethernet, Fast Ethernet, Gigabit Ethernet
Expansion / Connectivity	
<b>Interfaces</b>	1 x USB 3.1 (1 in front) 2 x USB 3.1 (2 rear) 4 x USB 2.0 (4 rear) 2 x LAN (Gigabit Ethernet) - RJ-45 (2 rear) 3 x Mini DisplayPort (3 rear)
Miscellaneous	
<b>Cables Included</b>	Mini DisplayPort-DisplayPort adapter (2 pcs.)
<b>Compliant Standards</b>	BSMI, EN 61000-3-2, NOM, EN 61000-3-3, EN55024, FCC Part 15 B Class A, KC, VCCI Class A, EAC, RCM, KN35, AS/NZS CISPR 32 Class A, KN32 Class A, EN 55032 Class A, IEC/EN/UL 60950-1, ICES-3(A)/NMB-3(A)
Power	
<b>Device Type</b>	Power supply - hot-plug
<b>Power Redundancy</b>	Yes
<b>Installed Qty</b>	2
<b>Max Supported Qty</b>	2
<b>Nominal Voltage</b>	AC 120/230 V (50/60 Hz)
<b>Power Provided</b>	495 Watt
Operating System / Software	
<b>OS Provided</b>	Windows 10 IoT Enterprise SAC
<b>Software</b>	AXIS Camera Station Core (32 channels licence)
Manufacturer Warranty	
<b>Service &amp; Support</b>	Limited warranty - 3 years
Dimensions & Weight	
<b>Width</b>	21.8 cm
<b>Depth</b>	60.3 cm
<b>Height</b>	43 cm
<b>Weight</b>	22.9 kg
Environmental Parameters	
<b>Min Operating Temperature</b>	10 °C
<b>Max Operating Temperature</b>	35 °C
<b>Humidity Range Operating</b>	10 - 80% (non-condensing)