

Produktinformation



Information

<i>Tillverkare</i>	Axis Communications
<i>Artnr</i>	0833-001

Axis C1004-E - IP speaker - for PA system - PoE - 6 Watt - 2-way - white

Axis C1004-E network cabinet speaker makes audio smart and easy, and opens up a wealth of possibilities. The speaker system is perfect for background music and for live and scheduled announcements in retail stores. Axis C1004-E can be mounted horizontally or vertically. Splash-proof construction means, it can be installed under the eaves, where it's not directly exposed to rain.

Specifikation

General

Product Type	IP speaker - for PA system
Media Content Source	Flash memory card
Microphone	Yes
Protection	Splashproof
Enclosure Colour	White
Enclosure Design	Bass reflex
Enclosure Material	Plastic, metal

Speaker System

Speaker Type	2-way - active
Nominal Output Power	6 Watt
Frequency Response	60 - 20000 Hz
Max Output Level (Max SPL)	96 dB
Amplifier	Integrated
Amplifier Class	D
Amplifier Output Power	6W
Coverage	130° x 100°
Interfaces	IEEE 802.3af (Power over Ethernet)
VoIP Protocols	SIP

Audio Formats	WAV, PCM, MP3, ADPCM
Speaker System Details	
Driver Details	Speaker: woofer driver - 4.72" Speaker: tweeter driver - 0.98" - balanced dome
Connections	
Connector Type	Network (RJ-45)
Miscellaneous	
Included Accessories	Mounting hardware, mounting bracket, AVHS authentication key, AXIS Camera Station licence key, cable shoe, AXIS Connector Guard A
Compliant Standards	EN 61000-3-2, EN 61000-3-3, EN55024, EN 61000-6-1, ICES-003 Class A, EN 61000-6-2, NEMA Type 3R, FCC Part 15 B Class A, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, EN 50121-4, IEC 62236-4, VCCI Class A, KN24, EN 55022 Class A, IEC EN60529, KN35, AS/NZS CISPR 32 Class A, EN 55032 Class A, KCC KN32 Class A, IEC/EN/UL 60950-1, IEC/EN/UL 60950-22
Power	
Power Source	Power over Ethernet (PoE)
Dimensions & Weight	
Width	19.6 cm
Depth	20 cm
Height	29 cm
Weight	3 kg
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years