

## Produktinformation



### Information

<i>Tillverkare</i>	Axis Communications
<i>Artnr</i>	5025-281

## AXIS T8129 PoE Extender - Repeater - 100Mb LAN - 10Base-T, 100Base-TX - RJ-45 / RJ-45 - up to 100 m

Ethernet has a limited cable length between the switch and the camera of 100 m. When needed to cover a longer distance, a switch is normally used as a repeater, or optical fiber may be used. To overcome this distance limit, network installers can simply connect an AXIS T8129 PoE Extender in-line with the Cat-5e or Cat-6 cable, and forward the rest to the camera. AXIS T8129 PoE Extender is compatible with all Axis network video products supporting PoE, and it is both IEEE 802.3af and IEEE 802.3at compliant.

## Specifikation

### General

<b>Device Type</b>	Repeater
<b>Form Factor</b>	External

### Networking

<b>Connectivity Technology</b>	Wired
<b>Cabling Type</b>	10Base-T, 100Base-TX
<b>Data Link Protocol</b>	10Mb LAN, 100Mb LAN
<b>Data Transfer Rate</b>	100 Mbps
<b>Max Transfer Distance</b>	100 m
<b>Status Indicators</b>	PoE, link/activity
<b>Compliant Standards</b>	IEEE 802.3af, IEEE 802.3at

### Expansion / Connectivity

<b>Interfaces</b>	2 x Ethernet 10Base-T/100Base-TX - RJ-45 female
-------------------	---

### Miscellaneous

<b>Compliant Standards</b>	Plug and Play, EN55024, EN55022 Class B, FCC Part 15 B, FCC, RoHS, WEEE
----------------------------	---

### Power

<b>Power Over Ethernet (PoE)</b>	PoE
Dimensions & Weight	
<b>Width</b>	10.5 cm
<b>Depth</b>	4 cm
<b>Height</b>	2.2 cm
<b>Weight</b>	45 g
Environmental Parameters	
<b>Min Operating Temperature</b>	-10 °C
<b>Max Operating Temperature</b>	50 °C
<b>Humidity Range Operating</b>	0 - 85% (non-condensing)