

## Produktinformation



### Information

<i>Tillverkare</i>	BIXOLON
<i>Artnr</i>	BCD-2000DSG

## BIXOLON BCD-2000 - Customer display - 100 cd/m<sup>2</sup> - RS-232, USB - dark grey - USB, serial RS-232

## Specifikation

### General

<b>Display Type</b>	Customer display / STN passive matrix
<b>Form Factor</b>	Desktop/pole
<b>Character Resolution</b>	4 lines x 30 characters
<b>Character Type</b>	95 alphanumeric characters, 6 international characters
<b>Character Font</b>	8 x 16, 9 x 17
<b>Character Height</b>	8.48 mm
<b>Character Width</b>	4.24 mm
<b>Brightness</b>	100 cd/m <sup>2</sup>
<b>Command Set</b>	UTC, ESC/POS
<b>Colour</b>	White on blue
<b>Colour</b>	Dark grey
<b>Image Colour Disclaimer</b>	The displayed product image may be a different colour
<b>Dimensions (WxDxH)</b>	22.04 cm x 10.54 cm x 52.8 cm
<b>Weight</b>	850 g

### Connectivity

<b>Interfaces</b>	USB Serial
-------------------	------------

### Mechanical

<b>Display Position Adjustments</b>	Height, pivot (rotation), tilt
<b>Rotation Angle</b>	360

### Miscellaneous

<b>MTBF</b>	50,000 hour(s)
-------------	----------------

Power

**Voltage Required** DC 5/24 V

Software / System Requirements

**Included Software** Drivers & Utilities

Environmental Parameters

**Min Operating Temperature** 0 °C

**Max Operating Temperature** 40 °C

**Humidity Range Operating** 10 - 80%