

## Produktinformation



### Information

<i>Tillverkare</i>	BIXOLON
<i>Artnr</i>	BCD-3000K

## BIXOLON BCD-3000 - Customer display - 100 cd/m<sup>2</sup> - RS-232, USB - black - USB, serial RS-232

## Specifikation

### General

<b>Display Type</b>	Customer display / STN passive matrix
<b>Form Factor</b>	Desktop
<b>Character Resolution</b>	2 lines x 20 characters
<b>Character Type</b>	95 alphanumeric characters, 6 international characters
<b>Character Font</b>	8 x 16
<b>Character Height</b>	9.6 mm
<b>Character Width</b>	4.8 mm
<b>Brightness</b>	100 cd/m <sup>2</sup>
<b>Command Set</b>	UTC, ESC/POS
<b>Colour</b>	White on blue
<b>Colour</b>	Black
<b>Image Colour Disclaimer</b>	The displayed product image may be a different colour
<b>Dimensions (WxDxH)</b>	13 cm x 6.85 cm x 11.03 cm
<b>Weight</b>	250 g

### Connectivity

<b>Interfaces</b>	USB Serial
-------------------	------------

### Mechanical

<b>Display Position Adjustments</b>	Tilt
<b>Tilt Angle</b>	0/+35

### Miscellaneous

<b>MTBF</b>	50,000 hour(s)
-------------	----------------

**Compliant Standards** Plug and Play

Power

**Voltage Required** DC 5 V

Software / System Requirements

**Included Software** Drivers & Utilities, OPOS Drivers

Environmental Parameters

**Min Operating Temperature** 0 °C

**Max Operating Temperature** 40 °C

**Humidity Range Operating** 10 - 80%