

Produktinformation



Information



<i>Tillverkare</i>	Cisco
<i>Artnr</i>	ATA192-3PW-K9

Cisco ATA 192 Multiplatform Analog Telephone Adapter - VoIP phone adapter - 2 ports - 100Mb LAN

Specifikation

General

Device Type	VoIP phone adapter
Width	10 cm
Depth	10 cm
Height	2.8 cm
Weight	132.1 g

Networking

Form Factor	External
Ports Qty	2
Connectivity Technology	Wired
Data Link Protocol	Ethernet, Fast Ethernet
Network / Transport Protocol	TCP/IP, PPTP, UDP/IP, L2TP, IPSec, PPPoE, ARP, RTP, RTCP
Remote Management Protocol	SNMP 3, HTTP, HTTPS, TFTP, SSH, TR-069
Status Indicators	Power, phone, Internet
Features	NAT support, Syslog support, DiffServ support, IPv6 support, SNTP support, wall mountable, port forwarding, reset button, LLDP support, DHCP client, Automated Attendant (IVR), Type of Service (ToS), Internet Control Message Protocol (ICMP), dual image support, Cisco Discovery Protocol
Encryption Algorithm	AES, TLS 1.1, TLS 1.2, ESP
Authentication Method	Secure Shell (SSH)
Compliant Standards	IEEE 802.1Q, IEEE 802.1p, IEEE 802.1ab (LLDP)

IP Telephony

VoIP Protocols	SIP, RTCP, RTP, SRTP
Voice Codecs	G.711, G.729a, G.729ab, G.711a, G.726, T.38, G.711μ
Telephony Interfaces	2 phone (FXS)
IP Telephony Features	Call forwarding, Caller ID, call waiting, call hold, distinctive ringing, call transfer, Do-not-disturb (DND) support, caller ID block/unblock
Expansion / Connectivity	
Interfaces	2 x FXS - RJ-11 2 x 100Base-TX - RJ-45
Miscellaneous	
MTBF	300,000 hours
Compliant Standards	FCC Part 15 B, EN 61000-4-4, EN 61000-4-2, EN 61000-4-3, EN 61000-4-6, EN 61000-4-5, EN 61000-4-11, EN 61000-4-8, IEC 60950-1:2005 Second Edition, EN 61000-3-3:2013, EN 55024:2010+A1:2015, Directive 2014/35/EU, Directive 2014/30/EU, UL 60950 Second Edition, CAN/CSA C22.2 No. 60950 Second Edition, ANSI C63.4-2014, AS/NZS 60950-1:2015, ICES-003:2016, EN 61000-3-2:2014 Class A, EN 55032:2015 Class B, AS/NZS CISPR32:2015 Class B, CISPR 32:2015 Class B
Power	
Power Device	External power adapter
Voltage Required	AC 120/230 V / DC 5 V (50/60 Hz)
Power Consumption Operational	5 Watt
Manufacturer Warranty	
Service & Support	Limited warranty - 1 year
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 90% (non-condensing)