

Produktinformation



Information



Tillverkare

Cisco

Artnr

C3KX-PWR-350WAC-REF

Cisco - Power supply - hot-plug / redundant (plug-in module) - AC 100-240 V - 350 Watt - for Catalyst 3560X-24, 3560X-48

Specifikation

General

Status	R4
Device Type	Power supply - hot-plug / redundant - plug-in module

Power Device

Input Voltage	AC 100-240 V
Frequency Required	50 - 60 Hz
Input Connectors	Power IEC 60320 C14
Power Capacity	350 Watt

Miscellaneous

MTBF	580,710 hours
Compliant Standards	BSMI, CISPR 22 Class A, GOST, CISPR 24, EN 61000-3-2, VCCI Class A ITE, EN 61000-3-3, EN55024, EN55022 Class A, CISPR 22, EN50082-1, EN 61000-6-1, EN 61000-4-4, EN 61000-4-2, EN 61000-4-3, EN 61000-4-6, EMC, MIC, ICES-003 Class A, EN 61000-4-5, RoHS, UL 60950-1, FCC Part 15 A, CSA C22.2 No. 60950-1, EN 300 386

Environmental Parameters

Min Operating Temperature	-5 °C
Max Operating Temperature	45 °C
Humidity Range Operating	5 - 90%

Dimensions & Weight

Width	8.3 cm
Depth	26 cm

Height	3.5 cm
Weight	1.25 kg

Compatibility Information

Designed For	Cisco Catalyst 3560X-24P-L, 3560X-24P-S, 3560X-24T-L, 3560X-24T-S, 3560X-48PF-L, 3560X-48PF-S, 3560X-48P-L, 3560X-48P-S, 3560X-48T-L, 3560X-48T-S
--------------	---