

## Produktinformation



### Information



Tillverkare

Cisco

Artnr

C3K-PWR-750WAC-REF

## Cisco - Power supply - hot-plug (plug-in module) - AC 100-240 V - 750 Watt - for Catalyst 2960, 2960S, 3560E, 3560V2

Cisco is the worldwide leader in networking for the Internet. Cisco provides the broadest line of solutions for transporting data, voice and video within buildings, across campuses, or around the world. Cisco solutions ensure that networks both public and private operate with maximum performance, security, and flexibility.

## Specifikation

### General

**Status** R4

**Device Type** Power supply - hot-plug - plug-in module

### Power Device

**Input Voltage** AC 100-240 V

**Frequency Required** 50 - 60 Hz

**Input Connectors** Power IEC 60320 C13

**Power Capacity** 750 Watt

### Miscellaneous

**Compliant Standards** FCC Class A certified, BSMI, CISPR 22 Class A, GOST, CISPR 24, NOM, VCCI Class A ITE, EN55024, EN55022 Class A, AS/NZS 60950-1, CCC, FCC Part 15, MIC, UL 60950-1, IEC 60950-1, EN 60950-1

### Environmental Parameters

**Min Operating Temperature** -5 °C

**Max Operating Temperature** 45 °C

**Humidity Range Operating** 10 - 85%

### Dimensions & Weight

**Width** 15.2 cm

Depth	29 cm
Height	4.2 cm
Weight	1.8 kg

Compatibility Information

Designed For	Cisco Catalyst 2960-24LC-S, 2960-24LT-L, 2960-24PC-L, 2960-24PC-S, 2960-24-S, 2960-24TC, 2960-24TC-L, 2960-24TC-S, 2960-24TT, 2960-48PST-L, 2960-48PST-S, 2960-48T, 2960-48TC, 2960-48TC-L, 2960-48TC-S, 2960-48TT, 2960-48TT-L, 2960-48TT-S, 2960-8TC, 2960-8TC-S, 2960S-24PD-L, 2960S-24PS-L, 2960S-24TD-L, 2960S-24TS-L, 2960S-24TS-S, 2960S-48FPD-L, 2960S-48FPS-L, 2960S-48LPD-L, 2960S-48LPS-L, 2960S-48TD-L, 2960S-48TS-L, 2960S-48TS-S, 3560E-24PD, 3560E-24TD, 3560E-48PD, 3560E-48PD-F, 3560E-48TD, 3560E-48TD-SD, 3560V2-24PS, 3560V2-24TS, 3560V2-24TS-SD, 3560V2-48PS, 3560V2-48TS
--------------	---