

Produktinformation



Information



<i>Tillverkare</i>	Cisco
<i>Artnr</i>	C3K-PWR-750WAC=

Cisco - Power supply - hot-plug (plug-in module) - AC 100-240 V - 750 Watt - for Catalyst 2960, 2960S, 3560E, 3560V2, 3750E

Cisco is the worldwide leader in networking for the Internet. Cisco provides the broadest line of solutions for transporting data, voice and video within buildings, across campuses, or around the world. Cisco solutions ensure that networks both public and private operate with maximum performance, security, and flexibility.

Specifikation

General

Device Type Power supply - hot-plug - plug-in module

Power Device

Input Voltage AC 100-240 V

Frequency Required 50 - 60 Hz

Input Connectors Power IEC 60320 C13

Power Capacity 750 Watt

Miscellaneous

Compliant Standards FCC Class A certified, BSMI, CISPR 22 Class A, GOST, CISPR 24, NOM, VCCI Class A ITE, EN55024, EN55022 Class A, AS/NZS 60950-1, CCC, FCC Part 15, MIC, UL 60950-1, IEC 60950-1, EN 60950-1

Environmental Parameters

Min Operating Temperature -5 °C

Max Operating Temperature 45 °C

Humidity Range Operating 10 - 85%

Dimensions & Weight

Width 15.2 cm

Depth 29 cm

Height 4.2 cm

Weight 1.8 kg

Compatibility Information

Designed For Cisco Catalyst 2960-24LC-S, 2960-24LT-L, 2960-24PC-L, 2960-24PC-S, 2960-24-S, 2960-24TC, 2960-24TC-L, 2960-24TC-S, 2960-24TT, 2960-48PST-L, 2960-48PST-S, 2960-48T, 2960-48TC, 2960-48TC-L, 2960-48TC-S, 2960-48TT, 2960-48TT-L, 2960-48TT-S, 2960-8TC, 2960-8TC-S, 2960S-24PD-L, 2960S-24PS-L, 2960S-24TD-L, 2960S-24TS-L, 2960S-24TS-S, 2960S-48FPD-L, 2960S-48FPS-L, 2960S-48LPD-L, 2960S-48LPS-L, 2960S-48TD-L, 2960S-48TS-L, 2960S-48TS-S, 3560E-24PD, 3560E-24TD, 3560E-48PD, 3560E-48PD-F, 3560E-48TD, 3560E-48TD-SD, 3560V2-24PS, 3560V2-24TS, 3560V2-24TS-SD, 3560V2-48PS, 3560V2-48TS, 3750E-24PD, 3750E-24TD, 3750E-48PD, 3750E-48PD-F, 3750E-48TD