


## Produktinformation



### Information

	
<i>Tillverkare</i>	Cisco
<i>Artnr</i>	CBW140AC-E

## Cisco Business 140AC - Radio access point - 802.11ac Wave 2 - Wi-Fi - 2.4 GHz, 5 GHz

The Cisco Business 140AC Access Point delivers powerful multi-user, multiple input, multiple output (MU-MIMO) (2x2) wireless in a compact form factor. Ideal for indoor Wi-Fi coverage, the Cisco Business 140AC delivers a highly secure and reliable wireless connection for small business workplaces. Compatible with Cisco Business 100 Series Mesh Extenders to rapidly expand your Wi-Fi network.

## Specifikation

### General

<b>Device Type</b>	Radio access point
<b>Width</b>	15.08 cm
<b>Depth</b>	15.08 cm
<b>Height</b>	3.3 cm
<b>Weight</b>	400 g

### Processor / Memory / Storage

<b>Processors Installed</b>	710 MHz
<b>RAM</b>	1 GB
<b>Flash Memory</b>	256 MB

### Networking

<b>Form Factor</b>	External
<b>Connectivity Technology</b>	Wireless
<b>Data Transfer Rate</b>	1 Gbps
<b>Data Link Protocol</b>	IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac Wave 2
<b>Frequency Band</b>	2.4 GHz, 5 GHz
<b>Performance</b>	Maximum data rate (2.4 GHz): 300 Mbps Maximum data rate (5 GHz): 867 Mbps

<b>Capacity</b>	Wireless clients per Wi-Fi radio: 200 Wireless clients: 400 VLANs supported: 16
<b>Status Indicators</b>	Status
<b>Features</b>	VLAN support, manageable, DFS support, wall mountable, Mesh networking, Wi-Fi Multimedia (WMM) support, RADIUS support, ceiling mountable, 802.1x authentication, MU-MIMO technology, SU-MIMO technology, Authentication, Authorization and Accounting (AAA)
<b>Encryption Algorithm</b>	AES, TLS, PEAP, TTLS, WPA2, WPA3
<b>Authentication Method</b>	RADIUS, MS-CHAP v.2, Extensible Authentication Protocol (EAP), EAP-FAST
<b>Compliant Standards</b>	IEEE 802.11b, IEEE 802.11a, IEEE 802.3af, IEEE 802.11d, IEEE 802.11g, IEEE 802.1x, IEEE 802.11i, IEEE 802.11h, IEEE 802.11n, IEEE 802.11r, IEEE 802.11ac Wave 2
Aerial	
<b>Antenna</b>	Internal
Expansion / Connectivity	
<b>Interfaces</b>	1 x 1000Base-T (PoE) - RJ-45
Miscellaneous	
<b>Included Accessories</b>	Torx security screw, ceiling rail mount clip, mounting bracket
<b>Compliant Standards</b>	VCCI, ICES-003, FCC Part 15.247, RSS-102, UL 2043, UL 60950-1, IEC 60950-1, EN 60950-1, FCC Part 15.107, FCC Part 15.109, FCC Part 15.407, ARIB STD-T66, ARIB STD-T71, EN 300 328, EN 50385, FCC OET Bulletin 65c, EN 301 489-1, RSS-247, EN 301 893, CAN/CSA-C22.2 No. 60950-1, EMI Class B, EN 301 489-17
Power	
<b>Power Over Ethernet (PoE) Supported</b>	PoE
<b>Power Consumption Operational</b>	8.3 Watt
Manufacturer Warranty	
<b>Service &amp; Support</b>	Limited warranty - replacement - lifetime
Environmental Parameters	
<b>Min Operating Temperature</b>	0 °C
<b>Max Operating Temperature</b>	50 °C
<b>Humidity Range Operating</b>	10 - 90% (non-condensing)