

Produktinformation



Information



<i>Tillverkare</i>	Cisco
<i>Artnr</i>	CP-6901-CL-K9=

Cisco Unified IP Phone 6901 Slimline - VoIP phone - SCCP - charcoal

The Cisco Unified IP Phone 6901 is a single-line endpoint delivering cost-effective access to Cisco unified communications. Designed with a trim line-like low profile, the Cisco Unified IP Phone 6901 is an ideal solution for lobbies, hallways, elevators, hotel bathrooms, or other settings that have an occasional need for voice communications services. The Cisco Unified IP Phone 6901 supports two incoming calls with call-waiting service. Fixed feature keys provide one-touch access to hold, redial, and call waiting. Transfer and conference can be supported by using the hook switch similar to that of traditional analog phones. The Cisco Unified IP Phone 6901 is an earth-friendly solution. As with the other Cisco Unified IP Phone 6900 Series endpoints, the Cisco Unified IP Phone 6901 takes advantage of reground and recyclable plastics for a more earth responsible solution.

Specifikation

General

Product Type	VoIP phone
Body Colour	Charcoal
Body Material	ABS plastic

Phone Features

Call Services	Voice Mail, Call Waiting, Call Forwarding, Call Transfer, Call Hold
Dialer Type	Keypad
Dialer Location	Base
Conference Call Capability	Yes
Speakerphone	Yes (digital duplex)
Function Buttons	Hold button, auto redial button
Volume Control	Yes
Ringer Control	Yes
Indicators	Voice message waiting indicator
Additional Features	Music on hold, built-in web server

IP Telephony

VoIP	Yes
VoIP Protocols	SCCP
Voice Codecs	G.729a, G.729ab, G.711u, G.711a
IP Address Assignment	DHCP, static
Power Over Ethernet (PoE) Support	Yes
Network Protocols	Cisco Discovery Protocol (CDP)
Network Ports Qty	1 x Ethernet 10/100Base-TX
Voice Features	Comfort noise generation (CNG), voice activity detection (VAD)
Memory	
RAM	32 MB
Miscellaneous	
Hearing Aid Compatible	Yes
Placing / Mounting	Wall-mountable, table-top
Also Included	8 MB
Compliant Standards	VCCI Class B ITE, CISPR 22 Class B, CISPR 24, EN 60950, EN 61000-3-2, IEC 60950, EN 61000-3-3, EN55024, UL 60950, EN50082-1, EN55022 Class B, ICES-003 Class B, EN 61000-6-1, ACA TS001, AS/NZS 60950-1, CSA C22.2 No. 60950-00, FCC CFR47 Part 68, FCC CFR47 Part 15 B
Dimensions & Weight (Base)	
Width	9.4 cm
Depth	4.6 cm
Height	20.5 cm
Weight	621 g
Manufacturer Warranty	
Service & Support	Limited warranty - 1 year