


Produktinformation



Cisco Unified IP Phone 6941 Standard - VoIP phone - SCCP - multiline - charcoal

Information

| | |
|--------------------|---|
| |  |
| <i>Tillverkare</i> | Cisco |
| <i>Artnr</i> | CP-6941-C-K9-REF |

The Cisco Unified IP Phone 6941 is an innovative IP endpoint that delivers affordable, business-grade voice communication services to customers worldwide. The Cisco Unified IP Phone 6941 supports four lines and a full-duplex speakerphone for a more productive, more flexible, and easier-to-use endpoint experience. The Cisco Unified IP Phone 6941 supports single-call per-line appearance, offering traditional telephony-like user experience for customers who seek this type of call interaction for their users. Fixed keys for hold, transfer, and conference; tri-color LED line and feature keys also make the phone simpler and easier to use. The Cisco Unified IP Phone 6941 is also more energy-efficient and eco-friendly, in support of customer green initiatives. A deep-sleep option provides energy savings. With this option, Cisco Unified IP Phone 6941 consumes up to 50-percent less power in off-hours versus when the phone is idle during normal business hours. In addition, reground and recyclable plastics deliver a more earth-responsible solution.

Specifikation

General

| | |
|----------------------|-------------|
| Status | R4 |
| Product Type | VoIP phone |
| Body Colour | Charcoal |
| Body Material | ABS plastic |

Phone Features

| | |
|-----------------------------------|---|
| Call Services | Voice Mail, Caller ID, Call Transfer, Call Hold |
| Dialer Type | Keypad |
| Dialer Location | Base |
| Conference Call Capability | Yes |
| Speakerphone | Yes (digital duplex) |
| Menu Operation | Yes |
| Function Buttons | Conference button, transfer button, hold button |
| Volume Control | Yes |
| Ringer Control | Yes |
| Ring Tones | 7 |
| Indicators | Voice message waiting indicator |
| Firmware Upgradable | Yes |

IP Telephony

| | |
|--|---|
| Main Features | Integrated Ethernet switch |
| VoIP | Yes |
| VoIP Protocols | SCCP |
| Voice Codecs | G.729a, G.729ab, G.711u, G.711a |
| Lines Supported | Multiline |
| Quality of Service | IEEE 802.1Q (VLAN), IEEE 802.1p |
| Power Over Ethernet (PoE) Support | Yes |
| Network Protocols | TFTP, Cisco Discovery Protocol (CDP) |
| Network Ports Qty | 2 x Ethernet 10Base-T/100Base-TX |
| Voice Features | Comfort noise generation (CNG), voice activity detection (VAD) |
| Display | |
| Type | LCD display - monochrome |
| Display Location | Base |
| Display Resolution | 396 x 162 pixels |
| Backlit | Yes |
| Display Languages | Danish, Hungarian, Czech, Croatian, Slovenian, Thai, Slovak, Brazilian Portuguese, English, German, French, Italian, Norwegian, Portuguese, Polish, Finnish, Swedish, Russian, Spanish, Dutch, Greek, Turkish, Bulgarian, Serbian, Catalan, Japanese, Chinese, Korean |
| Miscellaneous | |
| Connections | Headset jack |
| Hearing Aid Compatible | Yes |
| Placing / Mounting | Wall-mountable, table-top |
| Included Accessories | Power adapter |
| Compliant Standards | VCCI Class B ITE, CISPR 22 Class B, CISPR 24, EN 60950, EN 61000-3-2, IEC 60950, EN 61000-3-3, EN55024, UL 60950, EN50082-1, EN55022 Class B, ICES-003 Class B, EN 61000-6-1, ACA TS001, AS/NZS 60950-1, CSA C22.2 No. 60950-00, FCC CFR47 Part 68, FCC CFR47 Part 15 B |
| Power | |
| Type | Power adapter - external |
| Dimensions & Weight (Base) | |
| Width | 18.8 cm |
| Depth | 20.5 cm |
| Height | 16.4 cm |
| Weight | 1 kg |