

## Produktinformation



### Cisco Unified IP Conference Phone 8831 - Conference VoIP phone - SIP

#### Information



<i>Tillverkare</i>	Cisco
<i>Artnr</i>	CP-8831-EU-K9-REF

The Cisco Unified IP Conference Phone 8831 enhances people-centric communications, combining superior high-definition (HD) audio performance and 360-degree coverage for all sizes of conference rooms and executive offices. It provides an audiophile sound experience with a full-duplex two-way wideband (G.722) audio hands-free speaker. The IP Conference Phone 8831 is a simple, scalable solution that meets the challenges of the most diverse rooms. It provides flexible deployment options and expansion by using extension microphones that can be wired or wireless (Digital Equipment Cordless Telephone (DECT)) with a daisy-chain configuration of two units. The IP Conference Phone 8831 has an industrial design with enhanced ergonomics that puts the user first. It offers a detached control panel so that the display may be easily viewed without having to move the entire unit. It also provides easy view of device mute status from all sides.

## Specifikation

### General

<b>Status</b>	R4
<b>Product Type</b>	Conference VoIP phone
<b>Compatible Platforms</b>	Cisco Business Edition 3000, Cisco Business Edition 6000
<b>Body Material</b>	PC/ABS

### Phone Features

<b>Call Services</b>	Voice Mail, Caller ID, Call Waiting, Call Forwarding, Call Transfer, Call Hold, Message Waiting Capability
<b>Dialer Type</b>	Keypad
<b>Dialer Location</b>	Base
<b>Conference Call Capability</b>	Yes
<b>Speakerphone</b>	Yes (digital duplex)
<b>Menu Operation</b>	Yes
<b>Programmable Buttons Qty</b>	4
<b>Indicators</b>	Voice message waiting indicator, hold indicator, mute indicator
<b>Additional Functions</b>	Call timer, built-in clock
<b>Additional Features</b>	Noise reduction, music on hold

### Conference Phone

<b>Package Content</b>	Conference phone console, Conferencing base unit
<b>Features</b>	Echo cancellation

IP Telephony	
<b>Main Features</b>	Multiple VoIP protocol support
<b>VoIP</b>	Yes
<b>VoIP Protocols</b>	SIP
<b>Voice Codecs</b>	G.711, G.722, G.729a, G.729ab, iLBC
<b>Quality of Service</b>	IEEE 802.1Q (VLAN), IEEE 802.1p
<b>IP Address Assignment</b>	DHCP, static
<b>Security</b>	128 bit AES, IEEE 802.1X
<b>Power Over Ethernet (PoE) Support</b>	Yes
<b>Network Protocols</b>	TFTP, SRTP
<b>Network Ports Qty</b>	1 x Ethernet 10/100Base-TX
<b>Compatible Software</b>	Cisco Unified Communications Manager 7.1 or later
<b>Voice Features</b>	Comfort noise generation (CNG), voice activity detection (VAD), automatic gain control (AGC)
<b>Network Features</b>	Class 3 PoE, Lightweight Directory Access Protocol (LDAP)
Display	
<b>Type</b>	LCD display - monochrome
<b>Display Location</b>	Base
<b>Diagonal Size</b>	3.5"
<b>Display Resolution</b>	396 x 162 pixels
<b>Backlit</b>	Yes
<b>Display Languages</b>	Danish, Hebrew, Hungarian, Czech, Croatian, Slovenian, Thai, Slovak, Brazilian Portuguese, English, German, French, Italian, Norwegian, Portuguese, Polish, Finnish, Swedish, Russian, Spanish, Dutch, Greek, Turkish, Arabic, Bulgarian, Latvian, Lithuanian, Estonian, Serbian, Romanian, Catalan, Japanese, Chinese, Korean
Miscellaneous	
<b>Compliant Standards</b>	CISPR 24, BSMI CNS 13438 Class B, EN55024, EN55022 Class B, ICES-003 Class B, FCC Part 15 B, AS/NZS 60950-1, AS/ACIF S004, UL 60950-1 Second Edition, AS/NZS 3548 Class B, EN 301 406, FCC CFR47 Part 15 D, CSA C22.2 No. 60950-1 Second Edition, EN 60950-1 Second Edition, IEC 60950-1 Second Edition, GB 4943-2001 PSB, VCCI Class B
Dimensions & Weight (Base)	
<b>Width</b>	26.35 cm
<b>Depth</b>	5.08 cm
<b>Height</b>	15.05 cm
<b>Weight</b>	1.587 kg