

Produktinformation



Information



Tillverkare	Cisco
Artnr	GLC-FE-100BX-D-REF

Cisco - SFP (mini-GBIC) transceiver module - 100Mb LAN - 100Base-BX - LC single-mode - up to 10 km - 1550 nm - for Catalyst 3560, 65XX; Integrated Services Router 11XX

The Cisco 100BASE-BX10 SFPs operate on ordinary SMF single-strand link spans up to 10 kilometers long.

Specifikation

General

Status	R4
Device Type	SFP (mini-GBIC) transceiver module
Form Factor	Plug-in module

Networking

Connectivity Technology	Wired
Cabling Type	100Base-BX
Data Link Protocol	100Mb LAN
Optical Wave Length	1550 nm
Max Transfer Distance	10 km
Compliant Standards	IEEE 802.3, IEEE 802.3ah

Expansion / Connectivity

Interfaces	1 x Ethernet 100Base-BX - LC single-mode
Compatible Slots	1 x SFP (mini-GBIC)

Dimensions & Weight

Width	1.34 cm
Depth	5.65 cm
Height	8.5 mm

Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	50 °C

Compatibility Information

Designed For	Cisco Catalyst 3560-12PC, 3560-12PC-S, 3560-8PC, 6500, 6503, 6503 Firewall Security System, 6506, 6506 chassis, 6506 Firewall Security System, 6506-E, 6509, 6509 chassis, 6509 Firewall and IDS Security System, 6509 Firewall and VPN Security System, 6509 Wiring Closet Bundle, 6509-E, 6509-NEB, 6509-NEB-A, 6513, 6513 chassis Cisco Integrated Services Router 1111, 1112, 1113, 1116, 1117, 1118
--------------	--