

Produktinformation



Information



Tillverkare	Cisco
Artnr	GLC-FE-100FX=

Cisco - SFP (mini-GBIC) transceiver module - 100Mb LAN - 100Base-FX - LC multi-mode - up to 2 km - 1310 nm - for Catalyst 2960, 2960-24, 2960-48, 2960G-24, 2960G-48, 2960S-24, 2960S-48, 3560, 3560-12

The Cisco 100BASE-FX Small Form-factor Pluggable (SFP) is a hot-swappable input/output device that plugs into a Fast Ethernet port or slot, linking the port with the network. The Cisco 100BASE-FX SFP operates on ordinary multimode fiber-optic (MMF) link spans up to 2 kilometers long.

Specifikation

General

Device Type	SFP (mini-GBIC) transceiver module
Form Factor	Plug-in module

Networking

Connectivity Technology	Wired
Cabling Type	100Base-FX
Data Link Protocol	100Mb LAN
Optical Wave Length	1310 nm
Max Transfer Distance	2 km
Compliant Standards	IEEE 802.3, IEEE 802.3ah

Expansion / Connectivity

Interfaces	1 x Ethernet 100Base-FX - LC multi-mode x 2
Compatible Slots	1 x SFP (mini-GBIC)

Dimensions & Weight

Width	1.34 cm
Depth	5.65 cm
Height	8.5 mm

Manufacturer Warranty

Service & Support

Limited warranty - 90 days

Environmental Parameters

Min Operating Temperature

0 °C

Max Operating Temperature

50 °C

Compatibility Information

Designed For

Cisco Catalyst 2960-24LC-S, 2960-24PC-L, 2960-24PC-S, 2960-24TC, 2960-24TC-L, 2960-24TC-S, 2960-48PST-L, 2960-48PST-S, 2960-48T, 2960-48TC, 2960-48TC-L, 2960-48TC-S, 2960-8TC, 2960-8TC-S, 2960G-24TC, 2960G-48TC, 2960G-8TC, 2960S-24PD-L, 2960S-24PS-L, 2960S-24TD-L, 2960S-24TS-L, 2960S-24TS-S, 2960S-48FPD-L, 2960S-48FPS-L, 2960S-48LPD-L, 2960S-48LPS-L, 2960S-48TD-L, 2960S-48TS-L, 2960S-48TS-S, 3560-12PC, 3560-12PC-S, 3560-8PC