

## Produktinformation



### Information



Tillverkare	Cisco
Artnr	GLC-LX-SM-RGD=

## Cisco Rugged SFP - SFP (mini-GBIC) transceiver module - GigE - 1000Base-LX, 1000Base-LH - LC single-mode - 1310 nm - for Cisco 3270, 3270 Rugged Integrated Services Router Card

The industry-standard Cisco Small Form-Factor Pluggable (SFP) transceiver modules are hot-swappable input/output (I/O) devices that plug into 100BASE, 1000BASE and 10GBASE ports (for SFP+), which connect the module port with the fiber-optic or copper network. The 1000BASE-LX/LH SFP transceiver module for SMF, compatible with the IEEE 802.3z 1000BASE-LX standard, operates on standard singlemode fiber-optic link spans of up to 10 km and up to 550 m on any multimode fibers. When used over legacy multimode fiber type, the transmitter should be coupled through a mode conditioning patch cable.

## Specifikation

### General

Device Type	SFP (mini-GBIC) transceiver module
Form Factor	Plug-in module

### Networking

Connectivity Technology	Wired
Cabling Type	1000Base-LX, 1000Base-LH
Data Link Protocol	GigE
Data Transfer Rate	1 Gbps
Optical Wave Length	1310 nm

### Expansion / Connectivity

Interfaces	1 x Ethernet 1000Base-LX - LC single-mode x 2
Compatible Slots	1 x SFP (mini-GBIC)

### Manufacturer Warranty

Service & Support	Limited warranty - 1 year
-------------------	---------------------------

### Environmental Parameters

**Min Operating Temperature** -40 °C

**Max Operating Temperature** 85 °C

Compatibility Information

**Designed For** Cisco 3270, 3270 Rugged Integrated Services Router Card