

Produktinformation



Information



| | |
|--------------------|-----------------|
| <i>Tillverkare</i> | Cisco |
| <i>Artnr</i> | PWR-C1-1100WAC= |

Cisco - Power supply - hot-plug / redundant (plug-in module) - AC 115-240 V - 1100 Watt - for Catalyst 3850-48, 9300; ONE Catalyst 3850-48

Specifikation

General

Device Type Power supply - hot-plug / redundant - plug-in module

Power Device

Input Voltage AC 115-240 V
Frequency Required 50 - 60 Hz
Input Connectors Power IEC 60320 C16
Output Voltage -56 V
Power Capacity 1100 Watt

Miscellaneous

Features LED indicators

Compliant Standards TUV GS, CISPR 22 Class A, CISPR 24, cUL, EN55024, EN55022 Class A, CISPR 22, CCC, EMC, RoHS, UL 60950-1, IEC 60950-1, KCC, FCC Part 15 A, AS/NZS, VCCI Class A, CAN/CSA-C22.2 No. 60950-1

Environmental Parameters

Min Operating Temperature -5 °C
Max Operating Temperature 45 °C
Humidity Range Operating 10 - 95% (non-condensing)
Sound Emission 48 dBA

Dimensions & Weight

Width 8.3 cm
Depth 29.8 cm

Height 3.5 cm

Weight 1.4 kg

Compatibility Information

Designed For Cisco Catalyst 3850-48F-BA (1100 Watt), 3850-48F-E (1100 Watt), 3850-48F-L (1100 Watt), 3850-48F-S (1100 Watt), 9300 (1100 Watt), 9300 (Higher Scale) (1100 Watt), 9300L (1100 Watt) Cisco ONE Catalyst 3850-48F (1100 Watt)