

Produktinformation



Information



Tillverkare Cisco

Artnr PWR-C45-2800ACV-REF

Cisco - Power supply - hot-plug (plug-in module) - AC 200-240 V - 2800 Watt - for Catalyst 4503, 4503-E, 4504, 4506, 4506-E, 4507R, 4507R-E, 4510R, 4510R+E, 4510R-E

Specifikation

General

Status	R4
Device Type	Power supply - hot-plug - plug-in module

Power Device

Input Voltage	AC 200-240 V
Input Voltage Margin	+ 10% / - 10%
Frequency Required	50/60 Hz
Output Voltage	-50, +12, +3.3 V
Power Capacity	2800 Watt

Miscellaneous

Features	Integrated PoE
Compliant Standards	CISPR 22 Class A, EN 60950, EN 61000-3-2, EN55022, VCCI Class A ITE, IEC 60950, EN 61000-3-3, EN55024, EN55022 Class A, UL 60950, EN50082-1, CSA 22.2 No. 60950, AS/NZS 3260, ICES-003 Class A, AS/NZS 3548, FCC CFR47 Part 15, EN 300 386

Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 90%

Compatibility Information

Designed For	Cisco Catalyst 4503, 4503-E, 4503-E Data Bundle, 4503-E PoE Bundle, 4504, 4506, 4506-E, 4506-E PoE GE Bundle, 4507R, 4507R-
--------------	---

E, 4507R-E Data Bundle, 4507R-E PoE Bundle, 4510R, 4510R+E,
4510R-E