

## Produktinformation



### Information



<i>Tillverkare</i>	Cisco
<i>Artnr</i>	SNS-3615-K9

## Cisco Secure Network Server 3615 - rack-mountable - Xeon Silver 4110 2.1 GHz - 32 GB - HDD 600 GB

The Cisco Secure Network Server is a scalable solution that helps network administrators meet complex network access control demands by managing the many different operations that can place heavy loads on applications and servers. The Cisco Secure Network Server 3615 is designed for small deployments.

## Specifikation

### General

<b>Type</b>	Server
<b>Product Form Factor</b>	Rack-mountable - 1U
<b>Server Scalability</b>	2-way
<b>Hot-Swap Bays Qty</b>	8

### Processor / Chipset

<b>CPU</b>	Intel Xeon Silver 4110 / 2.1 GHz
<b>Number of Cores</b>	8-core
<b>CPU Qty</b>	1
<b>Max CPU Qty</b>	2
<b>CPU Upgradability</b>	Upgradable
<b>Processor Main Features</b>	Intel Execute Disable Bit, Enhanced Intel SpeedStep Technology, Intel Virtualization Technology
<b>CPU Socket</b>	LGA2011 Socket

### Cache Memory

<b>Installed Size</b>	L3 Cache - 11 MB
<b>Cache Per Processor</b>	11 MB

### RAM

<b>Installed Size</b>	32 GB
-----------------------	-------

<b>Technology</b>	DDR4 SDRAM
<b>Effective Memory Speed</b>	2400 MHz
<b>Memory Specification Compliance</b>	PC4-21300
<b>Features</b>	Single rank
<b>Configuration Features</b>	2 x 16 GB

#### Hard Drive

<b>Type</b>	HDD
<b>Capacity</b>	1 x 600 GB
<b>Interface Type</b>	SAS 12Gb/s
<b>Spindle Speed</b>	10000 rpm

#### Storage Controller

<b>Type</b>	1 x RAID
<b>Controller Interface Type</b>	SATA 6Gb/s / SAS 12Gb/s
<b>Channel Qty</b>	8
<b>RAID Level</b>	RAID 0
<b>Buffer Size</b>	2 GB

#### Monitor

<b>Monitor Type</b>	None.
---------------------	-------

#### Graphics Controller

<b>Graphics Processor</b>	Matrox G200e
<b>Video Memory</b>	256 MB
<b>Video Interfaces</b>	VGA

#### Networking

<b>Ethernet Ports</b>	2 x 10 Gigabit Ethernet, 4 x Gigabit Ethernet
<b>Ethernet Controller</b>	Intel I350
<b>Data Link Protocol</b>	Ethernet, Fast Ethernet, Gigabit Ethernet, 10 Gigabit Ethernet
<b>Remote Management Protocol</b>	IPMI 2.0, CLI

#### Expansion / Connectivity

<b>Bays</b>	8 (total) / 7 (free) x hot-swap 2.5"
<b>Slots</b>	1 (total) / 1 (free) x PCIe 2.0 x8 - half-length 1 (total) / 1 (free) x PCIe 2.0 x16 - half-length, full-height
<b>Interfaces</b>	2 x LAN (10Gigabit Ethernet) - RJ-45 4 x LAN (Gigabit Ethernet) - RJ-45 1 x KVM 1 x VGA 2 x USB 1 x serial - RJ-45 1 x management - RJ-45

#### Miscellaneous

<b>Compliant Standards</b>	CISPR 22 Class A, CISPR 24, EN55024, EN55022 Class A, AS/NZS 60950-1, ICES-003 Class A, UL 60950-1, EN 60950-1 Second Edition, IEC 60950-1 Second Edition, VCCI Class A, KN24, KN22
----------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Class A, GB4943.1-2001, CNS 13438 Class A, CAN/CSA C22.2 No. 60950-1 Second Edition, 21 CFR 1040 Second Edition, KN35, AS/NZS CISPR22 Class A, EN 300386, EN61000-3-3, EN61000-3-2

#### Power

<b>Device Type</b>	Power supply
<b>Power Redundancy</b>	Optional
<b>Power Redundancy Scheme</b>	1+1 (with optional power supply)
<b>Installed Qty</b>	1
<b>Max Supported Qty</b>	2
<b>Nominal Voltage</b>	AC 120/230 V (50/60 Hz)
<b>Power Provided</b>	770 Watt

#### Manufacturer Warranty

<b>Service &amp; Support</b>	Limited warranty - 90 days
------------------------------	----------------------------

#### Dimensions & Weight

<b>Width</b>	43 cm
<b>Depth</b>	72.4 cm
<b>Height</b>	4.32 cm

#### Environmental Parameters

<b>Min Operating Temperature</b>	0 °C
<b>Max Operating Temperature</b>	40 °C
<b>Humidity Range Operating</b>	10 - 90% (non-condensing)