

## Produktinformation



### Information



<i>Tillverkare</i>	Cisco
<i>Artnr</i>	SNS-3655-K9

## Cisco Secure Network Server 3655 - rack-mountable - Xeon Silver 4116 2.1 GHz - 96 GB - HDD 4 x 600 GB

The Cisco Secure Network Server is a scalable solution that helps network administrators meet complex network access control demands by managing the many different operations that can place heavy loads on applications and servers. The Secure Network Server 3655 has several redundant components such as hard disks and power supplies, making it suitable for larger deployments that require highly reliable system configurations.

## Specifikation

### General

<b>Type</b>	Server
<b>Product Form Factor</b>	Rack-mountable
<b>Server Scalability</b>	2-way

### Processor / Chipset

<b>CPU</b>	Intel Xeon Silver 4116 / 2.1 GHz
<b>Max Turbo Speed</b>	3 GHz
<b>Number of Cores</b>	12-core
<b>CPU Qty</b>	1
<b>Max CPU Qty</b>	2
<b>CPU Upgradability</b>	Upgradable
<b>CPU Socket</b>	LGA2011-v3 Socket

### Cache Memory

<b>Installed Size</b>	L3 Cache - 16.5 MB
<b>Cache Per Processor</b>	16.5 MB

### RAM

<b>Installed Size</b>	96 GB / 384 GB (max)
<b>Technology</b>	DDR4 SDRAM

<b>Slots</b>	24 (Total) / 18 (empty)
<b>Configuration Features</b>	6 x 16 GB
Hard Drive	
<b>Type</b>	HDD - hot-swap
<b>Capacity</b>	4 x 600 GB
<b>Interface Type</b>	SAS 12Gb/s
<b>Spindle Speed</b>	10000 rpm
<b>Features</b>	Hot-Plug Support
Storage Controller	
<b>Type</b>	1 x RAID
<b>Controller Interface Type</b>	SAS 12Gb/s
<b>RAID Level</b>	RAID 10
Optical Storage	
<b>Type</b>	No optical drive
Monitor	
<b>Monitor Type</b>	None.
Graphics Controller	
<b>Video Interfaces</b>	VGA
Networking	
<b>Ethernet Ports</b>	2 x 10 Gigabit Ethernet, 4 x Gigabit Ethernet
<b>Data Link Protocol</b>	Ethernet, Fast Ethernet, Gigabit Ethernet
Expansion / Connectivity	
<b>Bays</b>	Hot-swap 2.5"
<b>Interfaces</b>	4 x LAN (Gigabit Ethernet) - RJ-45 2 x LAN (10Gigabit Ethernet) 1 x KVM 2 x VGA 4 x USB 2 x serial - RJ-45 1 x management - RJ-45
Miscellaneous	
<b>Compliant Standards</b>	CISPR 22 Class A, CISPR 24, EN55024, AS/NZS 60950-1, ICES-003 Class A, UL 60950-1, EN 60950-1 Second Edition, IEC 60950-1 Second Edition, VCCI Class A, KN24, KN22 Class A, GB4943.1-2001, EN 55022 Class A, CAN/CSA C22.2 No. 60950-1 Second Edition, 21 CFR 1040 Second Edition, EN 300386, EN61000-3-3, EN61000-3-2
Power	
<b>Device Type</b>	Power supply - hot-plug
<b>Power Redundancy</b>	Yes
<b>Installed Qty</b>	2
<b>Max Supported Qty</b>	2
<b>Power Provided</b>	770 Watt
Manufacturer Warranty	

**Service & Support**

Limited warranty - advance hardware replacement - 90 days - response time: 10 days

Dimensions & Weight

**Width**

43 cm

**Depth**

75.6 cm

**Height**

4.32 cm

Environmental Parameters

**Min Operating Temperature**

5 °C

**Max Operating Temperature**

35 °C

**Humidity Range Operating**

10 - 90% (non-condensing)