

Produktinformation



Information



Tillverkare	Cisco
Artnr	X2-10GB-LRM-REF

Cisco X2 - X2 transceiver module - 10 GigE - 10GBase-LRM - SC multi-mode - up to 220 m - 1310 nm - for Catalyst 3560E-12, 3560E-24, 3560E-48

The Cisco 10GBASE X2 modules offer customers a wide variety of 10 Gigabit Ethernet connectivity options for data center, enterprise wiring closet, and service provider transport applications.

Specifikation

General

Status	R4
Device Type	X2 transceiver module
Form Factor	Plug-in module

Networking

Connectivity Technology	Wired
Cabling Type	10GBase-LRM
Data Link Protocol	10 GigE
Data Transfer Rate	10 Gbps
Optical Wave Length	1310 nm
Max Transfer Distance	220 m
Compliant Standards	IEEE 802.3ae

Expansion / Connectivity

Interfaces	1 x Ethernet 10GBase-LRM - SC multi-mode x 2
Compatible Slots	1 x X2

Dimensions & Weight

Width	3.6 cm
Depth	9.1 cm

Height 1.3 cm

Environmental Parameters

Min Operating Temperature 0 °C

Max Operating Temperature 40 °C

Compatibility Information

Designed For Cisco Catalyst 3560E-12D, 3560E-12SD-E, 3560E-12SD-S, 3560E-24PD, 3560E-24TD, 3560E-48PD, 3560E-48PD-F, 3560E-48TD, 3560E-48TD-SD