

Produktinformation



Dell EMC PowerEdge R640 - rack-mountable - Xeon Silver 4210 2.2 GHz - 32 GB - SSD 480 GB

Information



<i>Tillverkare</i>	Dell
<i>Artnr</i>	0JV10

The PowerEdge R640 is the ideal dual-socket! 1U platform for dense scale-out data center computing. The R640 combines density, performance and scalability to optimize application performance and data center density.

Specifikation

General

Type	Server
Bundled Services	3 Years ProSupport
Product Form Factor	Rack-mountable - 1U
Server Scalability	2-way
Hot-Swap Bays Qty	8
Colour	Black

Processor / Chipset

CPU	Intel Xeon Silver 4210 / 2.2 GHz
Max Turbo Speed	3.2 GHz
Number of Cores	10-core
CPU Qty	1
Max CPU Qty	2
CPU Upgradability	Upgradable
Processor Main Features	Intel Turbo Boost Technology 2

Cache Memory

Installed Size	13.75 MB
Cache Per Processor	13.75 MB

RAM

Installed Size	32 GB / 1.5 TB (max)
Technology	DDR4 SDRAM
Effective Memory Speed	2400 MHz
Rated Memory Speed	2933 MHz
Form Factor	DIMM 288-pin
Slots	24 (Total) / 23 (empty)
Features	Registered, dual rank
Configuration Features	1 x 32 GB
RAM Supported	12 TB Load-Reduced 1.5 TB registered 192 GB Non-Volatile 6 TB Optane DC Persistent

Hard Drive

Type	SSD - hot-swap - 2.5"
Capacity	1 x 480 GB
Interface Type	SATA

Storage Controller

Type	1 x RAID
Storage Controller Name	Dell PERC H730P
Buffer Size	2 GB

Optical Storage

Type	No optical drive
-------------	------------------

Monitor

Monitor Type	None.
---------------------	-------

Graphics Controller

Graphics Processor	Matrox G200eW3
Video Memory	16 MB
Video Interfaces	VGA

Networking

Ethernet Ports	2 x Gigabit Ethernet, 2 x 10 Gigabit Ethernet SFP+
Ethernet Controller	Broadcom BCM5720, Broadcom BCM57412
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet, 10 Gigabit Ethernet
Remote Management Controller	Integrated Dell Remote Access Controller 9 Enterprise (iDRAC9)

Expansion / Connectivity

Bays	8 (total) / 7 (free) x hot-swap 2.5"
Slots	2 PCIe 3.0 x16 - low-profile
Interfaces	2 x LAN (Gigabit Ethernet) - RJ-45 2 x USB 3.0 (2 rear) 1 x USB 2.0 (1 in front) 1 x USB 2.0 - micro-USB (1 in front) 1 x management (NIC) 1

x serial 2 x VGA (1 front, 1 rear) 2 x LAN (10Gigabit Ethernet) (SFP+) - RJ-45

Miscellaneous

Included Accessories	Rack sliding rails, bezel, riser card
Pricing Type	Build To Plan (BTP)

Power

Device Type	Power supply - hot-plug
Power Redundancy	Optional
Power Redundancy Scheme	1+1 (with optional power supply)
Installed Qty	1
Max Supported Qty	2
Nominal Voltage	AC 120/230 V (50/60 Hz)
Power Provided	750 Watt

Operating System / Software

OS Provided	No operating system
--------------------	---------------------

Dimensions & Weight

Width	48.2 cm
Depth	75.775 cm
Height	4.28 cm
Weight	21.9 kg

Environmental Parameters

Min Operating Temperature	10 °C
Max Operating Temperature	35 °C
Humidity Range Operating	10 - 80%