

## Produktinformation



### Dell UltraSharp U2719D - LED monitor - 27"

#### Information



|                    |             |
|--------------------|-------------|
| <i>Tillverkare</i> | Dell        |
| <i>Artnr</i>       | 210-ARBR-NB |

## Specifikation

### General

|                             |  |
|-----------------------------|--|
| Status                      | N2   |
| Display Type                | LED-backlit LCD monitor  |
| Energy Class                | Class A  |
| Energy Consumption per Year | 38 kWh   |
| Power Consumption (On mode) | 26 W   |
| Diagonal Size               | 27"  |
| Viewable Size               | 27"  |
| Built-in Devices            | USB 3.0 hub  |
| Aspect Ratio                | 16:9   |
| Native Resolution           | QHD 2560 x 1440 at 60 Hz   |
| Pixel Pitch                 | 0.233 mm   |
| Pixel Per Inch              | 109  |
| Brightness                  | 350 cd/m <sup>2</sup>  |
| Contrast Ratio              | 1000:1   |
| Colour Support              | 16.7 million colours   |
| Response Time               | 8 ms (normal); 5 ms (fast)   |
| Horizontal Viewing Angle    | 178  |
| Vertical Viewing Angle      | 178  |
| Screen Coating              | Anti-glare, 3H Hard Coating  |
| Backlight Technology        | LED backlight  |
| Features                    | Mercury free, 99.9% sRGB colour gamut, Dell Easy Arrange, 99% Rec 709 colour gamut, 85% DCI-P3 |

|  |   |
|--|---|
| <b>Dimensions (WxDxH)</b>              | 61.22 cm x 18 cm x 39 cm - with stand   |
| Connectivity                           |   |
| <b>Interfaces</b>                      | DisplayPort (HDCP) HDMI (HDCP) DisplayPort output (MST) 2 x USB 3.0 downstream 2 x USB 3.0 downstream with Battery Charging 1.2 USB 3.0 upstream Audio line-out (mini-jack) |
| Mechanical                             |   |
| <b>Display Position Adjustments</b>    | Height, pivot (rotation), swivel, tilt  |
| <b>Tilt Angle</b>                      | -5/+21  |
| <b>Swivel Angle</b>                    | 80  |
| <b>Height Adjustment</b>               | 130 mm  |
| <b>VESA Mounting Interface</b>         | Yes   |
| Miscellaneous                          |   |
| <b>Features</b>                        | Security lock slot (cable lock sold separately), VESA interface support, anti-theft stand lock slot   |
| <b>Compliant Standards</b>             | DisplayPort 1.4, HDCP 1.4   |
| <b>Security Slot Type</b>              | Kensington security slot  |
| Power                                  |   |
| <b>Voltage Required</b>                | AC 120/230 V (50/60 Hz)   |
| <b>Power Consumption Operational</b>   | 30 Watt   |
| <b>Power Consumption Stand by</b>      | 0.3 Watt  |
| <b>Power Consumption Sleep</b>         | 0.3 Watt  |
| <b>On / Off Switch</b>                 | No  |
| Software / System Requirements         |   |
| <b>Included Software</b>               | Dell Display Manager  |
| Dimensions & Weight                    |   |
| <b>Dimensions &amp; Weight Details</b> | With stand - width: 61.2 cm - depth: 18 cm - height: 39 cm Without stand - width: 61.22 cm - depth: 3.9 cm - height: 35.5 cm - weight: 3.92 kg                              |
| Dimensions & Weight (Shipping)         |   |
| <b>Shipping Weight</b>                 | 8.52 kg   |
| Environmental Standards                |   |
| <b>TCO Certified</b>                   | TCO Certified Displays 8  |
| <b>ENERGY STAR Certified</b>           | Yes   |
| Manufacturer Warranty                  |   |
| <b>Bundled Services</b>                | 3-Years Advanced Exchange Service and Premium Panel Guarantee   |
| Environmental Parameters               |   |
| <b>Min Operating Temperature</b>       | 0 °C  |
| <b>Max Operating Temperature</b>       | 40 °C   |

**Humidity Range Operating**

10 - 80% (non-condensing)