

Produktinformation



Dell UltraSharp U2719D - LED monitor - 27"

Information



<i>Tillverkare</i>	Dell
<i>Artnr</i>	210-ARBR

Specifikation

General

Status	N1
Display Type	LED-backlit LCD monitor
Energy Class	Class A
Energy Consumption per Year	38 kWh
Power Consumption (On mode)	26 W
Diagonal Size	27"
Viewable Size	27"
Built-in Devices	USB 3.0 hub
Aspect Ratio	16:9
Native Resolution	QHD 2560 x 1440 at 60 Hz
Pixel Pitch	0.233 mm
Pixel Per Inch	109
Brightness	350 cd/m ²
Contrast Ratio	1000:1
Colour Support	16.7 million colours
Response Time	8 ms (normal); 5 ms (fast)
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare, 3H Hard Coating
Backlight Technology	LED backlight
Features	Mercury free, 99.9% sRGB colour gamut, Dell Easy Arrange, 99% Rec 709 colour gamut, 85% DCI-P3

Dimensions (WxDxH)	61.22 cm x 18 cm x 39 cm - with stand
Connectivity	
Interfaces	DisplayPort (HDCP) HDMI (HDCP) DisplayPort output (MST) 2 x USB 3.0 downstream 2 x USB 3.0 downstream with Battery Charging 1.2 USB 3.0 upstream Audio line-out (mini-jack)
Mechanical	
Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Tilt Angle	-5/+21
Swivel Angle	80
Height Adjustment	130 mm
VESA Mounting Interface	Yes
Miscellaneous	
Features	Security lock slot (cable lock sold separately), VESA interface support, anti-theft stand lock slot
Compliant Standards	DisplayPort 1.4, HDCP 1.4
Security Slot Type	Kensington security slot
Power	
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	30 Watt
Power Consumption Stand by	0.3 Watt
Power Consumption Sleep	0.3 Watt
On / Off Switch	No
Software / System Requirements	
Included Software	Dell Display Manager
Dimensions & Weight	
Dimensions & Weight Details	With stand - width: 61.2 cm - depth: 18 cm - height: 39 cm Without stand - width: 61.22 cm - depth: 3.9 cm - height: 35.5 cm - weight: 3.92 kg
Dimensions & Weight (Shipping)	
Shipping Weight	8.52 kg
Environmental Standards	
TCO Certified	TCO Certified Displays 8
ENERGY STAR Certified	Yes
Manufacturer Warranty	
Bundled Services	3-Years Advanced Exchange Service and Premium Panel Guarantee
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C

Humidity Range Operating

10 - 80% (non-condensing)