

## Produktinformation



### Dell EMC PowerEdge T340 - tower - Xeon E-2224G 3.5 GHz - 16 GB - HDD 1 TB

#### Information



<i>Tillverkare</i>	Dell
<i>Artnr</i>	2NGPW

Develop your business with the PowerEdge T340 tower server. It is a reliable, easy to manage, and scalable one-socket server. The PowerEdge T340 helps you share and connect quickly across your organization to drive business results.

## Specifikation

### General

<b>Type</b>	Server
<b>Bundled Services</b>	3 Years Basic Onsite
<b>Product Form Factor</b>	Tower
<b>Built-in Devices</b>	System health and system ID indicator
<b>Server Scalability</b>	1-way
<b>Hot-Swap Bays Qty</b>	8
<b>Colour</b>	Black

### Processor / Chipset

<b>CPU</b>	Intel Xeon E-2224G / 3.5 GHz
<b>Max Turbo Speed</b>	4.7 GHz
<b>Number of Cores</b>	Quad-Core
<b>CPU Qty</b>	1
<b>Max CPU Qty</b>	1
<b>Processor Main Features</b>	Intel Turbo Boost Technology 2

### Cache Memory

<b>Installed Size</b>	8 MB
<b>Cache Per Processor</b>	8 MB

### RAM

<b>Installed Size</b>	16 GB / 64 GB (max)
<b>Technology</b>	DDR4 SDRAM - ECC
<b>Effective Memory Speed</b>	2666 MHz
<b>Rated Memory Speed</b>	2666 MHz
<b>Form Factor</b>	DIMM 288-pin
<b>Slots</b>	4 (Total) / 3 (empty)
<b>Configuration Features</b>	1 x 16 GB

#### Hard Drive

<b>Type</b>	HDD - hot-swap
<b>Capacity</b>	1 x 1 TB
<b>Interface Type</b>	SATA
<b>Spindle Speed</b>	7200 rpm

#### Storage Controller

<b>Type</b>	1 x RAID
<b>Storage Controller Name</b>	Dell PERC H330

#### Optical Storage

<b>Type</b>	DVD-Writer DVD-Writer
-------------	-----------------------

#### Monitor

<b>Monitor Type</b>	None.
---------------------	-------

#### Graphics Controller

<b>Graphics Processor</b>	Matrox G200eR2
<b>Video Memory</b>	16 MB
<b>Video Interfaces</b>	VGA

#### Networking

<b>Interface (Bus) Type</b>	LAN-on-motherboard (LOM)
<b>Ethernet Ports</b>	2 x Gigabit Ethernet
<b>Data Link Protocol</b>	Ethernet, Fast Ethernet, Gigabit Ethernet
<b>Remote Management Controller</b>	Integrated Dell Remote Access Controller 9 Express (iDRAC9)

#### Expansion / Connectivity

<b>Bays</b>	8 (total) / 7 (free) x hot-swap 3.5"
<b>Slots</b>	1 PCIe 3.0 x8 - half-length, full-height (x8 mode) 1 PCIe 3.0 x8 - half-length, full-height (x16 mode) 1 PCIe 3.0 x1 - half-length, full-height 1 PCIe 3.0 x4 - half-length, full-height (x8 mode)
<b>Interfaces</b>	4 x USB 2.0 - Type A 2 x LAN (Gigabit Ethernet) 1 x management (NIC) 2 x VGA (1 front, 1 rear) 1 x serial 3 x USB 3.0 - Type A (1 front, 2 rear) 1 x management - micro-USB (1 in front)

#### Miscellaneous

**Included Accessories**

Bezel

Power

**Device Type**

Power supply

**Power Redundancy**

Yes

**Power Redundancy Scheme**

1+1

**Installed Qty**

1

**Nominal Voltage**

AC 120/230 V (50/60 Hz)

**Power Provided**

495 Watt

Operating System / Software

**OS Provided**

No operating system

Dimensions & Weight

**Width**

30.79 cm

**Depth**

60.32 cm

**Height**

44.33 cm

**Weight**

25.25 kg

Environmental Parameters

**Min Operating Temperature**

10 °C

**Max Operating Temperature**

35 °C

**Humidity Range Operating**

10 - 80%