

Produktinformation



Dell - SFP (mini-GBIC) transceiver module - GigE - 1000Base-T - for Networking N3132, X1026, X1052; PowerEdge R440, R540, R740, R940, T440, T640

Information



<i>Tillverkare</i>	Dell
<i>Artnr</i>	407-BBOS

The Dell SPF transceiver delivers fiber connectivity to extend the range of your network. This hot-pluggable transceiver with SFP (Small Form Factor Pluggable) footprint features a duplex LC connector. The Dell networking 1000Base-T SPF transceiver provides 1000GbE connectivity up to 220 m. Additionally, it provides a unique enhanced digital diagnostic monitoring interface, which allows real-time access to device operating parameters such as transceiver temperature, laser bias current, transmitted optical power, received optical power, and transceiver supply voltage.

Specifikation

General

Device Type	SFP (mini-GBIC) transceiver module
Form Factor	Plug-in module

Networking

Connectivity Technology	Wired
Cabling Type	1000Base-T
Data Link Protocol	GigE

Compatibility Information

Designed For	Dell Force10 MXL blade, S4810 High-Performance, S55, S60, Z9000, Z9500 Dell Force10 ExaScale E-Series E1200i, E600i Dell Networking C7004, C7008, C9010, N2024, N2024P, N2048, N2048P, N3024, N3024F, N3024P, N3048, N3048P, N4032, N4032F, N4064, N4064F, S3048-ON, S4810-ON, S5000, S6000, S6000-ON, S6010-ON, X1018, X1018P, X4012 Dell PowerConnect 3424, 3424P, 3448, 3448P, 3524, 3524P, 3548, 3548P, 5524, 5524P, 5548, 5548P, 6224, 6224F, 6224P, 6248, 6248P, 7024, 7024F, 7024P, 7048, 7048P, 7048R, 7048RA, 8024F, M6220, M6348, M8024, M8024-k Dell PowerEdge C6320, FX2, T130, T330, T430, T630, VRTX Dell EMC Networking N3132PX-ON,
---------------------	--

X1026, X1026P, X1052, X1052P Dell EMC PowerEdge R440, R540,
R740, R740xd, R940, T440, T640