

## Produktinformation



### Dell P2419H - without stand - LED monitor - Full HD (1080p) - 24"

#### Information



<i>Tillverkare</i>	Dell
<i>Artnr</i>	DELL-P2419HWOS

Optimize your workspace with this efficient 23.8" monitor built with an ultrathin bezel design, a small footprint and comfort-enhancing features.

## Specifikation

### General

<b>Display Type</b>	LED-backlit LCD monitor / TFT active matrix
<b>Energy Class</b>	Class A
<b>Energy Consumption per Year</b>	29 kWh
<b>Power Consumption (On mode)</b>	20 W
<b>Diagonal Size</b>	24"
<b>Viewable Size</b>	23.8"
<b>Built-in Devices</b>	USB 3.0 hub
<b>Panel Type</b>	IPS
<b>Aspect Ratio</b>	16:9
<b>Native Resolution</b>	Full HD (1080p) 1920 x 1080 at 60 Hz
<b>Pixel Pitch</b>	0.275 mm
<b>Pixel Per Inch</b>	92
<b>Brightness</b>	250 cd/m <sup>2</sup>
<b>Contrast Ratio</b>	1000:1
<b>Colour Support</b>	16.7 million colours
<b>Response Time</b>	8 ms (normal); 5 ms (fast)
<b>Vertical Refresh Rate</b>	50 - 76 Hz
<b>Horizontal Refresh Rate</b>	30 - 83 kHz
<b>Horizontal Viewing Angle</b>	178

<b>Vertical Viewing Angle</b>	178
<b>Screen Coating</b>	Anti-glare, 3H Hard Coating
<b>Backlight Technology</b>	LED backlight
<b>OSD Languages</b>	Chinese (simplified), Brazilian Portuguese, English, German, French, Russian, Spanish, Japanese
<b>Features</b>	72% (CIE 1931) colour gamut, LED edgelight system, Dell Custom Color, Flicker Free technology, BFR/PVC-free, Mercury free, Dell ComfortView, arsenic free
<b>Dimensions (WxDxH)</b>	53.78 cm x 4.28 cm x 32.22 cm - without stand
<b>Weight</b>	3.26 kg
Connectivity	
<b>Interfaces</b>	DisplayPort VGA HDMI USB 3.0 upstream (Type B) 2 x USB 3.0 downstream (Type A) 2 x USB 2.0 downstream (Type A)
Mechanical	
<b>VESA Mounting Interface</b>	100 x 100 mm
Miscellaneous	
<b>Features</b>	Security lock slot (cable lock sold separately), LED indicator, VESA interface support
<b>Cables Included</b>	1 x DisplayPort cable - DisplayPort to DisplayPort 1 x SuperSpeed USB cable
<b>Compliant Standards</b>	Plug and Play, DDC/CI, RoHS, EDID compatible, DisplayPort 1.2
<b>Security Slot Type</b>	Kensington security slot
Power	
<b>Voltage Required</b>	AC 120/230 V (50/60 Hz)
<b>Power Consumption Operational</b>	18 Watt
<b>Power Consumption Stand by</b>	0.3 Watt
<b>Power Consumption (Off Mode)</b>	0.3 Watt
Software / System Requirements	
<b>Included Software</b>	Dell Display Manager
Dimensions & Weight	
<b>Dimensions &amp; Weight Details</b>	Without stand - width: 53.78 cm - depth: 4.28 cm - height: 32.22 cm - weight: 3.26 kg
Dimensions & Weight (Shipping)	
<b>Shipping Weight</b>	5.43 kg
Environmental Standards	
<b>TCO Certified</b>	TCO Certified Displays 8
<b>ENERGY STAR Certified</b>	Yes
Manufacturer Warranty	

<b>Bundled Services</b>	3-Years Advanced Exchange Service and Premium Panel Guarantee
Environmental Parameters	
<b>Min Operating Temperature</b>	0 °C
<b>Max Operating Temperature</b>	40 °C
<b>Humidity Range Operating</b>	20 - 80% (non-condensing)