

Produktinformation



Dell P2720DC - LED monitor - 27"

Information



<i>Tillverkare</i>	Dell
<i>Artnr</i>	DELL-P2720DC

Do more with a 27" QHD USB-C monitor that expands your workspace. Get a better view of all your important tasks while reducing cable clutter.

Specifikation

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class A+
Energy Consumption per Year	34 kWh
Power Consumption (On mode)	23 W
Diagonal Size	27"
Viewable Size	27"
Built-in Devices	USB 3.0 hub
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	QHD 2560 x 1440 at 60 Hz
Pixel Pitch	0.233 mm
Pixel Per Inch	108
Brightness	350 cd/m ²
Contrast Ratio	1000:1
Colour Support	1.07 billion colours
Response Time	8 ms (normal); 5 ms (grey-to-grey)
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare 3H hardness

Backlight Technology	WLED
Bezel Type	Flat front
Features	LED edgelight system, Energy Gauge, Mercury free, arsenic-free glass
Dimensions (WxDxH)	61.16 cm x 18.5 cm x 39.53 cm - with stand
Connectivity	
Interfaces	DisplayPort (DisplayPort 1.2 mode) HDMI USB-C DisplayPort output (DisplayPort 1.2 mode)
Mechanical	
Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Tilt Angle	-5/+21
Swivel Angle	90
Rotation Angle	180
Height Adjustment	130 mm
VESA Mounting Interface	100 mm, VESA
Miscellaneous	
Features	Security lock slot (cable lock sold separately), VESA interface support
Cables Included	1 x DisplayPort cable - DisplayPort to DisplayPort 1 x SuperSpeed USB-C cable
Power	
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	24.5 Watt
Power Consumption Stand by	0.3 Watt
Power Consumption Sleep	0.3 Watt
On / Off Switch	No
Software / System Requirements	
Included Software	Dell Display Manager
Dimensions & Weight	
Dimensions & Weight Details	Without stand - width: 61.16 cm - depth: 4.36 cm - height: 36.41 cm - weight: 4.97 kg With stand - width: 61.16 cm - depth: 18.5 cm - height: 39.53 cm
Dimensions & Weight (Shipping)	
Shipping Weight	9.53 kg
Environmental Standards	
TCO Certified	TCO Certified Displays 8
ENERGY STAR Certified	Yes
Manufacturer Warranty	
Bundled Services	3 years Advanced Exchange Service

Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 90% (non-condensing)